



**VENTURO**  
**BY GRUPPO GAMMA**


**FIELD WATCH III**

**OPERATING INSTRUCTIONS**

## About the Field III

The third iteration of Venturo's signature field watch line, the Field III is our smallest watch to date with a 40mm case, but with the same quality of materials and workmanship that Gruppo Gamma is known for.

Case:	Stainless steel, brushed, diameter 40mm
Crystal:	Sapphire, box shaped, anti-reflective
Dial:	With luminous hands and markers
Movement:	Seiko Instruments NH38A
Functions:	Hour, minute, second
Water resistance:	200m/ 660ft



## **Fastening & Unfastening Crown**

- To unfasten, turn crown anticlockwise until it pops out.
- To fasten, turn crown clockwise while pressing it against the case. Don't over-tighten; there's no need to.

## **Setting the Time**

- Pull unfastened crown out to position B.
- Turn the crown to set the time, then push crown back to Position A.

## **Winding**

- Flick the timepiece sideways to swing the rotor. When the timepiece is on your wrist, your arm movements will automatically wind the movement. Audible spinning of the rotor is normal.

- Alternatively, unfasten crown to winding position and give it a few turns clockwise until the timepiece starts running.

### **Opening & Closing the Bracelet Clasp**

- The clasp is locked by compression. To open, release the safety flap and then flick open the clasp using reasonable force.
- To close the clasp, press down until you hear a clicking sound.

### **Sizing & Removing the Bracelet**

- Removable links on the bracelet are secured using screw bars. To remove and install them, use a 1.2mm slotted screwdriver.
- Micro-adjustment can be done by moving the end links to the other mounting holes located on the clasp. The end links are mounted to the clasp using spring bars. To remove and install them, use a spring bar tool.
- To remove the bracelet from the watch head, press the quick release levers on the end links.

## **General Care**


- Don't wear or store your timepiece with the crown unfastened, and don't operate the crown when your timepiece is wet. After swimming, rinse it in fresh water.
- Steam and vapour can penetrate the case and damage your timepiece. Don't expose it to temperature extremes or corrosive chemicals, or wear it in saunas.
- Don't place timepiece near loudspeakers or other equipment that generate strong magnetic fields that may affect its precision.

## **Aftersales Support**

- This timepiece is warranted against manufacturing defects for 2 years. For assistance, contact us at [info@gruppogammawatches.com](mailto:info@gruppogammawatches.com).

## Gruppo Gamma Watch Tool

- The tool can be separated into 2 pieces by unscrewing it in the middle.
- Unscrew the caps to reveal a tool bit on each end.
- Each tool bit can be used for use as screwdriver, spring bar fork, or pin.



\* Earlier versions are fitted with 1.6mm screwdriver instead, for use with Mk I Nexus models