SWEETVINYL



SugarCube SC-2 Mini

Vinyl Recording Platform with Click & Pop Removal

The SC-2 Mini integrates the latest version 2.0 recording functions from the top-of-the-line SC-2 in a smaller form factor.

The SC-2 Mini is SweetVinyl's best value as it incorporates Discogs-based Album Metadata Tagging as well as easy to use track splitting; push-button recording, USB-3 port for USB drives, & LCD display along with all the features of the SC-1 Mini.

Rear panel features gold-platted RCA connectors, an RJ-45 Ethernet port, and USB-A connections.

The SC-2 Mini provides hours of enjoyment from previously unplayable LPs in any collection, while creating digital copies in virtually any digital format. The SC-2 Mini's flawless Click & Pop removal process benefits from the latest algorithm update with version 2.0 software which also includes SweetVinyl's latest LP recording system.

The iOS, Android, and laptop apps provide remote control of the Click & Pop removal and device bypass. The recording and track splitting functions work best from the laptop app.

The front-panel USB3 port will accommodate any USB storage device for saving recordings in any digital format (except DSD.)

The soundstage is virtually indistinguishable when engaged or in Analog Bypass.

SC-2 Mini In Brief

- 2.0 Click and Pop Algorithm
- 192K/24 Bit AKM A/D-D/A
- Device Bypass via Internal Relay
- Adjustable Removal Strength
- Click and Pop Removal Monitor
- Gold Plated RCA Interconnects
- iOS, Android, and Web Apps
- Front-panel Pairing with App
- LCD Graphics Display
- USB3-A Front-panel Port
- USB2-A Rear-panel Ports
- RJ45 Ethernet Port
- USB WiFi Adapter
- Excellent Build Quality
- Compact Size
- Black Only

SWEETVINYL



SugarCube SC-2 Mini

SPECIFICATIONS

Electronics

Line-In Maximum Level = +20 dBu (7.7 Vrms) Line-Out Level = Line-In level THD+N = 0.0025% (A-weighted) Frequency Response = 10Hz to 60kHz DC in = 5 volts, center-pin positive Average Power Dissipation = 8 watts

General

Dimensions: WxHxD: 8" x 8" x 3.5" Weight: 6 pounds (7 lbs. in box)

Connections

2x Line-In RCA (Left–Right) 2x Line-Out RCA (Left–Right) 1x USB3-A Front-panel (for USB Storage) 4x USB2-A Rear-panel 1x Ethernet: Gigabit

Recording

Sample rates: 44.1k, 48k, 88.2k, 96k, 176.4k, 196k bit width: 16, 24 formats: WAV, AIFF, FLAC, ALAC, MP4, AAC, MP3 Internal workspace: holds up to 8 album sides Output via USB3 frontpanel or LAN to workstation Automatic online access to album metadata; semi-automated track spliting

"Goodbye Clicks & Pops, Hello Mint Vinyl"