



CARRYALL 1500

IntelliTrak $^{\text{TM}}$ automatically senses the terrain and shifts power for maximum traction. Combined with a 2000-pound towing capacity and automotive-style rear suspension, the Carryall 1500 can handle any job.









Capacity 1450 lbs

Horsepower 20 hp (gasoline) 20 hp (diesel)



CARRYALL 1500 *Intellitach*

OUR MOST VERSATILE UTV

The same automatic 4WD system as our Carryall 1500 plus exclusive IntelliTach™ quick-change hydraulic tool attachment system. It's a mini forklift to help you do your best work.







Max Speed 25 mph

Max Vehicle

Horsepower 20 hp (diesel)



CARRYALL 1700 §

AND HAULS CARGO

With automatic four-wheel drive, four seats, and a full-size truck bed, Carryall 1700 can haul more cargo and passengers to places others fear to tread.







Max Vehicle Capacity 1600 lbs

Horsepower 20 hp (gasoline) 20 hp (diesel)



Intellitach

KEEP YOUR ESSENTIALS READY

Reduce the need for expensive construction equipment and get a variety of jobs done quickly with our exclusive IntelliTach™ quick-change tool attachment system.





Front Bucket

Pallet Forks

Plow Blade



2500 lb Winch

Windshield (solid and fold-down available)

representative for details.

Ask your Club Car sales

OPTIONS & ACCESSORIES



Canopy



Heavy-Duty Brushguard



Strobe Light



High Capacity Updgrade



CARRYALL 1500





CARRYALL 1700





/ =		DI	E	51	ΞI

ENGINE	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade	Kubota D722, industrial grade	Kawasaki 4-cycle, industrial grade	Kubota D722, industrial grade	
HORSEPOWER	20.1 hp (15 kW) rated © 3400 RPM per SAE J1349	20 hp (15 kW) rated © 3600 RPM per SAE J1995	20 hp (15 kW) rated @ 3600 RPM per SAE J1995	20.1 hp (15 kW) rated @ 3400 RPM per SAE J1349	20 hp (15 kW) rated @ 3600 RPM per SAE J1995	
BATTERIES	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	12-volt 500 CCA 105 min reserve	
STEERING	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	Rack and pinion with tilt steering	
FRONT SUSPENSION	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	Independent double A-arms with coil-over shocks	
REAR SUSPENSION	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	Semi-independent, 4-link solid axle	
BRAKES	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk	Twin piston front, single piston rear hydraulic disk	
PARK BRAKE	Mechanical disk	Mechanical disk	Mechanical disk	Mechanical disk	Mechanical disk	
TIRES	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	Standard All-terrain, 25 x 11-12, 4-ply Optional Mud, 25 x 11-12, 6-ply	
BED LxWxH	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	48.8 x 49.8 x 10.9 in (124 x 127 x 28 cm)	
WHEELBASE	82 in (208 cm)	82 in (208 cm)	82 in (208 cm)	114 in (290 cm)	114 in (290 cm)	
GROUND CLEARANCE	8.2 in (21 cm)	8.2 in (21 cm)	7.3 in (19 cm) - under differential 11.1 in (28 cm) - under floorboard	8.2 in (21 cm)	8.2 in (21 cm)	
FUEL TANK CAPACITY	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	6.5 gal (24.6 L)	
CURB WEIGHT	1430 lb (649 kg)	1550 lb (703 kg)	1751 lb (794 kg)	1630 lb (739 kg)	1750 lb (794 kg)	
BED CAPACITY	Standard 800 lb (363 kg); With HD Suspension 1050 lb (476 kg)	Standard 800 lb (363 kg); With HD Suspension 1050 lb (476 kg)	Standard 800 lb (363 kg)	800 lb (363 kg)	800 lb (363 kg)	
PAYLOAD CAPACITY	Standard 1200 lb (544 kg); With HD Suspension 1450 lb (658 kg)	Standard 1200 lb (544 kg); With HD Suspension 1450 lb (658 kg)	Standard 1200 lb (544 kg)	1600 lb (726 kg)	1600 lb (726 kg)	
TOWING CAPACITY	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	2000 lb (907 kg)	
OVERALL HEIGHT	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	80.3 in (204 cm)	
OVERALLLENGTH	124.6 in (317 cm)	124.6 in (317 cm)	121 in (307 cm) - w/o attachment arm and w/ cylinders stored 136 in (345 cm) - w/ attachment arm and cylinder fully extended 155 in (394 cm) - max extended position	154 in (391 cm)	154 in (391 cm)	
OVERALL WIDTH	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	58.5 in (149 cm)	
SPEED RANGE	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	25 mph (40.2 km/h)	
LIMITED WARRANTY	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	1 yr/1000 hr limited vehicle warranty 2 yr/2000 hr limited powertrain warranty	

Dark Gray Dark Green



Standard Colors (Molded-in)