

CamDo
Connect more Do more



CamDo's BLINK X time lapse and motion detection controller is designed for use with GoPro Hero 8, 7, 6 & 5 Black, Hero 5 Session, and also BackBone Ribcage modified cameras.

BLINK X powers down the camera between shots to save power. New improvements include increased power saving, more advanced date scheduling and the ability to **manually download images or upload and view images remotely using CamDo Cloud X system.**

Any WiFi enabled device can be used to configure up to 10 separate schedules including email using the BLINK X app. Schedules can also be programmed when using the BLINK X Band sensor motion detector.

By removing the camera battery the Blink X can be used to reboot the camera in case of failure. BLINK X includes a 2.5mm jack input for a wired remote trigger and a 3.5mm jack connecting to the optional X-Band motion detector.

BLINKX TIME LAPSE CONTROLLER IS IDEAL FOR:

Construction Timelapse
Season timelapse
Ocean / Glacier monitoring, etc
Film / Broadcast Timelapse

Features:

- Compatible with GoPro **Hero 8, Hero 7, Hero 6, Hero 5 Black** cameras, **Hero 5 Session**, plus BackBone Modified Ribcage Cameras
- Works with CamDo solar and dry housings X and Band motion detector
- Improved quick and simple web based interface
- Complete control to programme up to 10 different schedules via WiFi interface
- Future date start option
- Onboard Real Time Clock (2 years unpowered)
- GoPro status information also via interface
- 10X lower power consumption than Blink
- Universal strap mount
- External power supply if required
- BLINKX works with SolarX & Dry Enclosures
- Also Included:
 - CamDo custom USB-C Camera - BLINK X cable **(DO NOT USE ALTERNATIVES)**
 - USB OTG cable (for updates)

Specifications:

Blink X Power Usage	WiFi ON	52 mW
	WiFi OFF	0.25 mW
	Motion Detector Active (WiFi OFF)	12 mW
USB-C	Camera Connector	(USE NO ALTERNATIVES)
Micro USB Interface	External camera power	Firmware update
LED Indicator	Provides feedback information during operation and firmware updates	
2.5mm Input	Accepts wired remote or other custom trigger	
3.5mm Accessory Input	For optional X-Band motion detector	
Dimensions	65 x 44 x 13mm	
Weight	32 grammes (excluding cables)	
Compatible Cameras	GoPro Hero 8, Hero 7, Hero 6, Hero 5 Black, Hero5 Session. Also BackBone H7PRO, H5PRO H5M12 and H5 Ripcord cameras	

FULL SET UP AND TROUBLESHOOTING DETAILS ARE AVAILABLE ON THE CAMDO WEBSITE.

Please contact SeeSense for further details and technical advice for this and all of the GoPro compatible solutions and enhancements that we offer:

www.seesense.eu sales@seesense.eu

Rev: 4.26.1219 E.&O.E.