



















Place the ACRYLIC SQUARES (PART D) on either side of the **MOUNTING BLOCK** (PART E) and secure to the MOUNTING **BLOCK** (shiny side facing inwards) with the BLACK SCREWS (PART A). Refer to Fig A for correct orientation.



into the top holes of the ACRYLIC SQUARES. Take the NUTS (PART B) and with the rounded side facing out, partially thread onto BLACK SCREWS. Refer to Fig B. Repeat Steps 1 and 2 for the other MOUNTING BLOCK.

Put 2 BLACK SCREWS



Fig. B

BLAZE HORIZONTAL SLIDER



Remove the 2 silver screws from the top of your BLAZE lighting fixture. Now screw the MOUNTING BLOCK onto the BLAZE lighting fixture using SILVER SCREW (PART C).

Refer to Fig C for correct orientation. Repeat on the other side with the second MOUNTING BLOCK.



Fig. C

Carefully slide your
BLAZE lighting fixture by
aligning the NUTS of the
MOUNTING BLOCK into
the tracks of your RAIL
MOUNTING SYSTEM
(sold separately).
*NOTE' The easiest way of doing this is by

(Sold separately).

*NOTE' The easiest way of doing this is by laying the BLAZE lighting fixture on a flat surface and sliding the RAIL into the fixed MOUNTING BLOCKS.

Refer to Fig D.

4



Fig. D



*Vitamini strip lighting and rotatable mounts sold separately.







