

Contract Foam Underlay

PLF0010-50

Contact
 +44 (0) 1524 481 118
 info@plusfloor.com
 plusfloor.com

Product Information

Construction	IXPE Foam
Product Range	PlusFloor Accessories
Thickness	1mm
Roll Size	50m ² per roll
Width	1m

Performance

Tensile Stress (n)	GB/T 528	MD:3.5 TD:3
Tensile Strength (Mpa)	GB/T 528	MD:0.6 TD:0.5
Elongation (%)	GB/T 528	MD:100 TD:100
Thickness (mm)	0.9 - 1.1	
Magnification (times)	14-7	
Underfloor Heating	EN12524	Suitable - Max. 27° C
Hardness	Shore C/IS	30-40



Installation and Warranty

All PlusFloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. PlusFloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by PlusFloor, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this document, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.