

plusfloor

Formation Click

Luxury rigid vinyl plank

Well established as the go-to 'rigid click' system vinyl in the UK, our click lock flooring is a tried and tested system that works.

Quick and simple to install, for those jobs where time really does matter, our click lock construction is a must for those jobs where a real wood floor just won't cut it. With our Truegrain finish as standard your feet won't be able to tell the difference

Plusfloor Formation Click



White Washed PLF4250



French Loft PLF4254



Clouded Ice PLF4266



Pastel Blanc PLF4252



Pure Oyster PLF4260



Silvery Clay PLF4262



Warm Hessian PLF4256



Blanched Carbon PLF4264



Bronzed Urbane PLF4258



Burnt Cocoa PLF4268

Plusfloor Formation Click

Product Details

Product Codes PLF4250 - PLF4268 **Format** 1-Strip Plank **Finish** TrueGrain **Profile** Butt **Edge Profile** Bevelled **Thickness** 4.2mm ±0.2mm Width 180mm ±0.10mm Length 1220mm Wear Layer 0.3mm **Pack Size** 2.64m2

Installation & Maintenance

Fully Bonded Yes

Nailed No

Floated on underlay Yes (Recommended)

Over underfloor heating Yes

Technical Criteria

| Origin | Asia | |
|-----------------------------|-------------------|-----------------|
| Product Density | EN436 | 2000KG/M3 |
| Impact Test | ≤10mm | 5.5mm |
| Formaldehyde Emmission | El | |
| Slip Test | EN 13893 | Class DS |
| Fire Classification | EN 13501-1 | Bfl-s1 |
| Squareness | EN 427 | ≤0.25mm |
| Straightness | EN 427 | ≤0.25mm |
| Deviation to Edge | ≤2.0mm | |
| Deviation Embossed | ≤2.0mm | |
| Stability- Exposure to Heat | EN434 ≤0.15% | (800C, 6HR) |
| Curling | EN434 ±1.0mm | (800C, 6HR) |
| Abrasion Resistance | EN-660-2 | ≤0.015g |
| Acoustic Reduction | ISO 24343 | 16dB |
| Redisual Indentation | ISO 24343- 1:2007 | Pass (0.15mm) |
| Castor Chair Test | ISO/TR 4987:2009 | Pass |
| Peel Strength | ≥5.5kg | 11.6Kg |
| Click Strength | ≥10kg | 19.8Kg |
| Colour Fastness to Light | ISO 105 B02:1994 | Pass (Grade 6+) |
| Water Tightness | EN13553 | Pass |
| Slip Rating | 36+PTV | Wet |
| Warranty (year) | 20 Residential | 5 Commercial |

The warranty covers manufacturing defects and premature wear in the event of normal use.

Installation & Warranty

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Plusfloor, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.



www.plusfloor.com info@plusfloor.com T: +44(0)1524 481118