

## Product Details

Format	1-Strip Plank	
Finish	TrueGrain	
Profile	Butt	
Edge Profile	Bevelled	
Thickness	4.2mm	±0.2mm
Width	180mm	±0.10mm
Length	1220mm	
Wear Layer	0.3mm	
Pack Size	2.64m <sup>2</sup>	

## Installation & Maintenance

Fully Bonded	Yes
Nailed	No
Floated on underlay	Yes (Recommended)
Over underfloor heating	Yes

## Technical Criteria

Origin	Asia	
Product Density	EN436	2000KG/M <sup>3</sup>
Impact Test	≤10mm	5.5mm
Formaldehyde Emmission	E1	
Slip Test	EN 13893	Class DS
Fire Classification	EN 13501-1	Bfl-s1
Squareness	EN 427	≤0.25mm
Straightness	EN 427	≤0.25mm
Deviation to Edge	≤2.0mm	
Deviation Embossed	≤2.0mm	
Stability- Exposure to Heat	EN434 ≤0.15%	(800C, 6HR)
Curling	EN434 ±1.0mm	(800C, 6HR)
Abrasion Resistance	EN-660-2	≤0.015g
Acoustic Reduction	ISO 24343	16dB
Redisual Indentation	ISO 24343- 1:2007	Pass (0.15mm)
Castor Chair Test	ISO/TR 4987:2009	Pass
Peel Strength	≥5.5kg	11.6Kg
Click Strength	≥10kg	19.8Kg
Colour Fastness to Light	ISO 105 B02:1994	Pass (Grade 6+)
Water Tightness	EN13553	Pass
Slip Rating	36+PTV	Wet
Warranty (year)	20 Residential	5 Commercial

*The warranty covers manufacturing defects and premature wear in the event of normal use.*

## Installation & Warranty

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Plusfloor, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.