

Product Details

Format	Vinyl Tile	
Finish	Stone Effect	
Profile	Butt	
Edge Profile	Bevelled	
Thickness	2.5mm	EN ISO 24346
Width	330mm	
Length	660mm	
Wear Layer	0.55mm	EN ISO 24340
Pack Size	3.47m ² /box	16pcs/box

Technical Criteria

Origin	Europe	
Level of use	EN ISO 10874	23 - 33 - 42
Inflammability	EN 13501	Bfl-S1
Scratch resistance	EN ISO 660-2	Class T
Squareness	EN ISO 24342	≤ 0,25 mm
Straightness	EN ISO 24342	≤ 0,35 mm
Slip resistance	EN 13893	DS
Slip restraint	DIN 51130	R10
Residual indentation	EN ISO 24343-1	≤ 0,10 mm
Furniture leg resistance	EN ISO 16581	No damage
Curling	EN ISO 23999	≤ 2mm
Electrical resistance	EN 1081	≤ 109 Ohm
Dimensional stability	EN ISO 23999	Norm: ≤ 0,25 %
Heat insulation	EN ISO 10456	0,25 w/(m.K)
Thermal resistance R	EN 12664	< 2 kV
Electrostatic performance	EN 1815	
Formaldehyde group	EN 717-1	E1
Acoustic insulation	EN ISO 717-2	4 dB
Castor chair resistance	EN ISO 4918	No damage
Stain resistance	EN ISO 26987	Very good
Light fastness	EN ISO 105-B02	≥6
Underfloor heating	EN 12524	Max 27°C
Warranty (year)	20 Residential	10 Commercial

The warranty covers manufacturing defects and premature wear in the event of normal use.

Installation & Warranty

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Plusfloor, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.