


New Viileä

Carpet Tile


Contact
 +44 (0) 1524 481 118
 info@plusfloor.com
 plusfloor.com



Shadow Grey
PLF200



Pebble Grey
PLF201



Night Grey
PLF202



Cloud Grey
PLF203

Product

Surface Texture	Tufted loop pile	
Pile Fibre	100% Solution Dyed Nylon	
Tile Backing	Bitumen	
Pile Weight	ISO 8543	500 g/m ² (+/- 5%)
Pile Height	3.2-3.6mm	
Total Thickness	ISO 1765	5.4mm (+/- 5%)
Total Weight	ISO 8543	4100 g/m ² (+/- 7.5%)
Tile Size	500 x 500 x 5.4mm	
Tiles Per Box	20	5m ² coverage

Technical

Use Classification	Method EN 1307	Class 33
Castor Chair Test	EN 985	A, Continuous Use
Dimensional Stability	EN 986	Pass
Thermal Isolation	ISO 8302	0.06 m ² K/W
Sound Absorption	ISO 140-8	24 DB
Walk On Test - Static Loading	ISO 6356	< -0.3 kV Antistatic
Reaction to fire	EN ISO 11925-1	BFL-S1
Hot metal nut test	BS 4790	Low radius
Light Fastness	ISO 105 B02	>5
Warranty	15 Years (Commercial)	


Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by **PlusFloor**, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this document, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.




Sandstone
PLF204




Storm Blue
PLF205




Earth Brown
PLF206



Sea Blue
PLF207



Summer Red
PLF208



Leaf Green
PLF209