


Composition Tiles

Contact
 +44 (0) 1524 481 118
 info@plusfloor.com
 plusfloor.com

Loose Lay Vinyl Plank



Plank
 600 x 600 x 5mm

Product

Fixing	Loose Lay	
Profile	Butt Joint	
Format	1-Strip	
Finish	Embossed	
Edge	Square	
Wear Layer	0.55mm	
Slip Rating	R10	
Pack Size	2.57m ²	8 planks per box

Technical

Slip Resistance	36+ PTV (wet)	BS 7976-2 DIN51130
Water Resistance	Resistant	
Stain Resistance	Resistant	EN 423
Scratch Resistance	MSR-A2	EN 16094
Underfloor Heating	Suitable, max. 29°C	
Inflammability	Bfl-S1	EN 13501
Squareness	≤ 0.20mm	
Straightness	≤ 0.30mm	
Residual Indentation	~ 0.03mm	EN ISO 24343-1
Curling	≤ 2mm	
Dimensional Stability	≤ 0.15mm%	
Thermal Resistance R	0.039m ² K/W	EN 12667
Formaldehyde Group	E1	EN 717-1:2014
Castor Chair Resistance	Resistant	EN ISO 4918
Light Fastness	≥6	EN ISO 105-B02
Sound Impact Insulation	12 dB	ISO 10140-1:2016 ISO 717-2:2013
Static Electrical Propensity	Antistatic (≤ 2 kV)	EN 1815
Warranty (Years)	30 (Residential)	10 (Commercial)



Sereno
 PLF4306



Pewter
 PLF4307

Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by **PlusFloor**, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this document, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.