


# Elements Herringbone

**Contact**  
 +44 (0) 1524 481 118  
 info@plusfloor.com  
 plusfloor.com

## Click Lock Vinyl Herringbone

### Product

Fixing	Click Lock
Finish	SoftGrain embossing
Profile	Uni-Drop
Edge	Bevelled
Wear Layer	0.3mm
Pack Size	1.8m <sup>2</sup>




**Herringbone**  
750 x 150 x 5mm

**Nickel Oak**  
PLF5201CH


### Technical

Slip Resistance	36+ PTV (wet)	EN13893
Water Resistance	Resistant	
Stain Resistance	Resistant	
Sound Reduction	19 db lw (including underlay)	
Underlay	1mm	IXPE
Underfloor Heating	Suitable, max. 27°C	
Inflammability	Bfl-S1	EN 13501-1 EN9239-1
Reaction to Fire	B-S1-D0	EN11925-2:2020
Residual Indentation	0.01mm	TS EN ISO 2434-1:
Dimensional Stability	Class 34	TS EN ISO 23999
Thermal Resistance R	0.296 W/m <sup>2</sup> K	EN 12667
Formaldehyde Group	E1	EN 717-1
Antibacterial	ISO 2216	
Electrostatic Behaviour	Antistatic floor covering	1815:2016
Phthalate Analysis	Phthalate Free	In-house method
Surface Treatment (UV)	Yes	
Performance Classification	23, 34, 43	
Warranty (Years)	20 (Residential)	5 (Commercial)



**Iron Oak**  
PLF5203CH

**Calcium Oak**  
PLF5204CH



**Actinium Oak**  
PLF5206CH

**Copper Oak**  
PLF5207CH

### Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by **PlusFloor**, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this document, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.