
PlusFloor.

Vero Herringbone

Glue Down Vinyl Herringbone

Contact +44 (0) 1524 481 118 info@plusfloor.com plusfloor.com



Herringbone 380 x 95 x 2.5mm

Product

Fixing	Glue Down	Glue Down	
Finish	TrueGrain emb	TrueGrain embossing	
Profile	Butt Joint	Butt Joint	
Edge	Bevelled	Bevelled	
Wear Layer	0.55mm		
Pack Size	0.87m ²	24 planks per box	

Technical

Slip Resistance	36+ PTV (wet)	BS 7976-2 DIN51130
Water Resistance	Resistant	
Stain Resistance	Resistant	EN 423
Scratch Resistance	MSR-A2	EN 16094
Underfloor Heating	Suitable, max. 29°C	
Inflammability	Bfl-S1	EN 13501
Squareness	≤ 0.20mm	
Straightness	≤ 0.30mm	
Residual Indentation	~ 0.03mm	EN ISO 24343-1
Curling	≤ 2mm	EN ISO 23999
Dimensional Stability	≤ 0.15mm%	EN ISO 23999
Thermal Resistance R	0.039m ² K/W	EN 12667
Formaldehyde Group	E1	EN 717-1:2014
Castor Chair Resistance	Resistant	EN ISO 4918
Light Fastness	≥6	EN ISO 105-B02
Static Electrical Propensity	Antistatic (≤ 2 kV)	EN 1815
LRV	PLF7000GH	40.68%
	PLF7002GH	25.43%
	PLF7004GH	32.43%
	PLF7006GH	18%
	PLF7008GH	15.27%
	PLF7010GH	14.51%
	PLF7012GH	30.85%
Warranty (Years)	30 (Residential)	10 (Commercial)



Florence PLF7100GH



Venice PLF7104GH



Portofino PLF7106GH



Pompeii PLF7102GH



Sorrento PLF7112GH



Catania PLF7108GH



Tuscany

Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.