
Versailles

Glue Down Vinyl Panel



Panel 610 x 610 x 2.5mm

Product

Fixing	Glue Down	
Finish	TrueGrain embossing	
Profile	Butt Joint	
Edge	Bevelled	
Wear Layer	0.55mm	
Pack Size	4.46m ²	12 panels per box

Technical

Slip Resistance	36+ PTV (wet)	BS 7976-2 DIN51130
Water Resistance	Resistant	
Stain Resistance	Resistant	EN 423
Scratch Resistance	MSR-A2	EN 16094
Underfloor Heating	Suitable, max. 29°C	
Inflammability	Bfl-S1	EN 13501
Squareness	≤ 0.20mm	
Straightness	≤ 0.30mm	
Residual Indentation	~ 0.03mm	EN ISO 24343-1
Curling	≤ 2mm	EN ISO 23999
Dimensional Stability	≤ 0.15mm%	EN ISO 23999
Thermal Resistance R	0.039m ² K/W	EN 12667
Formaldehyde Group	E1	EN 717-1:2014
Castor Chair Resistance	Resistant	EN ISO 4918
Light Fastness	≥6	EN ISO 105-B02
Static Electrical Propensity	Antistatic (≤ 2 kV)	EN 1815
LRV	PLF7000	30.26%
	PLF7002	20.98%
	PLF7004	15.29%
	PLF7006	31.62%
Warranty (Years)	30 (Residential)	10 (Commercial)

PlusFloor.

Contact +44 (0) 1524 481 118 info@plusfloor.com plusfloor.com



Bordeaux PLF7006



Lyon PLF7000



Marseilles PLF7002



Dijon PLF7004

Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.