


# Shush!

**Contact**  
 +44 (0) 1524 481 118  
 info@plusfloor.com  
 plusfloor.com

## Glue Down Plank with Integrated Underlay

### Product

Format	Plank with Integrated Underlay
Fixing	Glue Down
Finish	TrueGrain Embossing
Profile	Butt Joint
Edge	Bevelled
Wear Layer	0.55mm
Pack Size	2.75m <sup>2</sup> , 12pcs
Sound Reduction	19dB



**1-Strip Plank**  
 1227 x 187 x 3.7mm



**Cashmere**  
 PLF4315SH

### Technical

Inflamability	BFL-S1	EN 13501-1
Scratch Resistance	MSR-A2	EN16094
Squareness	≤ 0.20mm	
Straightness	≤ 0.30mm	
PTV (Wet)	> 36	BS 7976-2 2002+A1:2013
Slip Resistance	R10	DIN 51130
Residual Indentation	- 0.03mm	ISO 24343-1
Curling	≤ 2mm	
Dimensional Stability	≤ 0.15%	EN ISO 23999
Thermal Resistance	0.039 (m <sup>2</sup> K)/W	EN 12667
Formaldehyde Group	E1	EN 717-1
Castor Chair Resistance	Pass	ISO 4918
Stain Resistance	Resistant	EN 423
Water Resistant	Yes	
Light Fastness	≥ 6	EN ISO 105-B02
Static Electrical Propensity	Antistatic (≤ 2 kV)	EN 1815
Warranty (Years)	30 (Residential)	10 (Commercial)



**Bordeaux**  
 PLF7006SH



**Pompeii**  
 PLF7102SH



**Catania**  
 PLF7108SH



**Sorrento**  
 PLF7112SH

### Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by **PlusFloor**, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this document, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.