

# High Density Underlay

PLF0012

**Contact**  
 +44 (0) 1524 481 118  
 info@plusfloor.com  
 plusfloor.com

## Product Information

Closed cells UHD polyethylene foam used for installation of class 2 LVT	
Antislip surface for locking system protection.	
Perfect for floor heating - highly exceeds minimum heat conduction value recommended by MMFA.	
Construction	High Density Polyethylene w/ anti slip layer
Product Range	PlusFloor Accessories
Thickness	1.2mm
Roll Size	50m <sup>2</sup> per roll
Width	1m
Area Weight	0.21kg/m <sup>2</sup>
Density	130kg/m <sup>2</sup>
Recyclable	Yes
Eco-friendly	Yes



## Performance

Reflected Walking Sound	8%	IHD-W431
Impact Sound Reduction	16dB	EN ISO10140, ISO717-2
Temporary Loads		
Resistance	200kPa	EN 826:2013+A: FU1:2019
Static Loads (Furniture)		
Resistance	>50kPa	EN1606
Dynamic Loads (Walking)		
Resistance	>100000 cycles	EN13793
Local Unevenness		
Compensation	0.95mm	EN-ISO868
Thermal Insulation	0,024m <sup>2</sup> K/W	EN12667:2002 at 24 C
Protection Against Moisture	<75m	EN12086
Protection Against		
Falling Objects	800mm	EN13329, EN438
Reaction To Fire	EN ISO11925-2	PN-EN13501-1

### Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by **PlusFloor**, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this document, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.