



plusfloor

Ranch Sawn

Distressed character with warmth and style

Sawing, brushing and planing techniques of a distressed floorboard are perfectly replicated in our new Sawn Collection. This dramatic look brings the warmth and style of the British countryside to any space. Choose from our four carefully selected colours which all give the impression of hundreds of years of use, without compromising on warranty.

Plusfloor

Ranch Sawn



Melrose

PLF4205GD



Cartmel

PLF4210GD



Eton

PLF4215GD



Black Lake

PLF4220GD

Product Details

Product Codes	PLF4205GD-PLF4220GD	
Format	1 Strip Plank	EN ISO 24342
Finish	TrueGrain	
Profile	Butt	
Edge Profile	Bevelled	
Thickness	2.5mm	EN ISO 24346
Width	200 mm	±0.10mm
Length	1325mm	
Wear Layer	0.55mm	EN ISO 24340
Pack Size	3.62m ² /box	8pcs/box
Weight	15.04kg	EN ISO 23997

Installation & Maintenance

Fully Bonded	Yes
Nailed	No

Technical Criteria

Origin	Europe	
Level of use	EN ISO 10874	23 - 33 - 42
Inflammability	EN 13501	Bfl-s1
Scratch resistance	EN ISO 660-2	Class T
Squareness & straightness	EN ISO 24342	≤0.35mm
Residual indentation	EN ISO 24343-1	≤0.10mm
Furniture leg resistance	EN ISO 16581	
Curling	EN ISO 23999	≤ 2 mm
Electrical resistance	EN 1081	≤ 109 Ohm
Dimensional stability	EN ISO 23999	
Slip Rating	36+ PTV	
Heat insulation	EN ISO 10456	0,25 w/(m.K)
Thermal resistance R	EN 12664	0,0100 m ² .K/W
Electrostatic performance	EN 1815	< 2 kV
Formaldehyde group	EN 717-1	E1
Acoustic insulation	EN ISO 717-2	4 dB
Castor chair resistance	EN ISO 4918	
Stain resistance	EN ISO 26987	Very good
Light fastness	EN ISO 105-B02	≥6
Underfloor heating	EN 12524	Suitable, max 27°C
Warranty (year)	20 Residential	10 Commercial

The warranty covers manufacturing defects and premature wear in the event of normal use.

Installation & Warranty

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Plusfloor, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.

plusfloor
Luxury vinyl

www.plusfloor.com

info@plusfloor.com

T: +44(0)1524 481118

Part of The Havwoods International Group