

Product Details

| | | |
|--------------|-------------------------|--------------|
| Format | 1 Strip Plank | EN ISO 24342 |
| Finish | TrueGrain | |
| Profile | Butt | |
| Edge Profile | Bevelled | |
| Thickness | 2.5mm | EN ISO 24346 |
| Width | 200 mm | ±0.10mm |
| Length | 1325mm | |
| Wear Layer | 0.55mm | EN ISO 24340 |
| Pack Size | 3.62m ² /box | 8pcs/box |
| Weight | 15.04kg | EN ISO 23997 |

Installation & Maintenance

| | |
|--------------|-----|
| Fully Bonded | Yes |
| Nailed | No |

LRV Ratings

| | |
|--------------|-------------|
| Name: | LRV: |
| Melrose | 33 |
| Cartmel | 15 |
| Eton | 11 |
| Black Lake | 6 |

Technical Criteria

| | |
|---------------------------|-------------------------------------|
| Origin | Europe |
| Level of use | EN ISO 10874 23 - 33 - 42 |
| Inflammability | EN 13501 Bfl-s1 |
| Scratch resistance | EN ISO 660-2 Class T |
| Squareness & straightness | EN ISO 24342 ≤0.35mm |
| Residual indentation | EN ISO 24343-1 ≤0.10mm |
| Furniture leg resistance | EN ISO 16581 |
| Curling | EN ISO 23999 ≤ 2 mm |
| Electrical resistance | EN 1081 ≤ 109 Ohm |
| Dimensional stability | EN ISO 23999 |
| Slip Rating | 36+ PTV |
| Heat insulation | EN ISO 10456 0,25 w/(m.K) |
| Thermal resistance R | EN 12664 0,0100 m ² .K/W |
| Electrostatic performance | EN 1815 < 2 kV |
| Formaldehyde group | EN 717-1 E1 |
| Acoustic insulation | EN ISO 717-2 4 dB |
| Castor chair resistance | EN ISO 4918 |
| Stain resistance | EN ISO 26987 Very good |
| Light fastness | EN ISO 105-B02 ≥6 |
| Underfloor heating | EN 12524 Suitable, max 27°C |
| Warranty (year) | 20 Residential 10 Commercial |

The warranty covers manufacturing defects and premature wear in the event of normal use.

Installation & Warranty

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Plusfloor, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.