

## Product Details

Format	Vinyl Tile
Finish	Stone Effect
Profile	Butt
Edge Profile	2 Sided With Integrated Grout Line
Thickness	2.5mm
Width	305mm
Length	610mm
Wear Layer	0.55mm
Pack Size	3.34m <sup>2</sup> /box

## Installation & Maintenance

Fully Bonded	Yes
Nailed	No
Floated on Underlay	No
Over Underfloor Heating	Yes

## Technical Criteria

Dimensions	ISO 24342	Length: ≤0.15% Width: ≤10% (MAX: 0.5mm)
Squareness	ISO 24342	≤ 400mm : ≤0.25mm > 400mm : ≤0.35mm
Overall thickness	ISO 24346	+0.13mm/0.10mm
Wear Layer thickness	ISO 24340	+13%/10%
Total mass per unit(g/m <sup>2</sup> )	ISO 23997	+13%/10%
Dimensional stability	ISO 23999	≤  0.25  %
Curling after exposure to heat	ISO 23999	≤  2.0  %
Residual indentation	ISO 24343-1	≤ 0.1mm
Effect of Castor chair	ISO 4918	No damage After 25,000 rev
Colour Fastness	ISO 105- BO2:M2	≤ 6
Slip Resistance	EN13893 DIN 51130	DS R10
Fire Behavior	EN 13501-1	Bf1-s1
Thermal Resistance	EN 12667	0.01(m <sup>2</sup> k)/W
Indoor Air Quality		IAC GOLD
Warranty (year)	30 Residential	10 Commercial

*The warranty covers manufacturing defects and premature wear in the event of normal use.*

## Installation & Warranty

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Plusfloor, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.