

Sound Barrier Underlay

PLF0006-15

Contact
 +44 (0) 1524 481 118
 info@plusfloor.com
 plusfloor.com

Product Information

Construction	High performance acoustic underlay for glue down and click LVT installations.
Product Range	PlusFloor Accessories
Thickness	1mm
Roll Size	15m ² per roll
Width	1m

Performance

Impact sound reduction	ISO 10140-3	$\Delta L_w = 24\text{dB}$
Reflective Sound Walking	31%	
Compressive Strength	>280 kPa	
Water Vapour Diffusion		
Resistance Factor	>114 SD	
Thermal Resistance R	0.04m ² K/W $T_{og} 0.4$	
Underfloor Heating	EN12524	Suitable - Max. 27° C
Mould and Mildew Resistant	Yes	



Installation and Warranty

All **PlusFloor** floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. **PlusFloor's** warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by **PlusFloor**, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this document, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.