

Product Details

Product Codes	PLF4300 – PLF4305
Format	Wood Loose Lay Vinyl
Finish	Embossed
Profile	Butt
Edge Profile	Bevelled
Thickness	5mm
Width	180mm
Length	1220mm
Wear Layer	0.5mm
Pack Size	2.16m ²

Technical Criteria

Dimensional Stability	EN 434	Pass
Flexibility	EN 435	Pass
Color Fastness	ISO 105-B02	Above 6
Abrasion Resistance	Class T	EN 660-2
Slip Resistance	< 0.3	EN 13501-1
	R10	DIN 51130
Castor Chair Resistance	EN 425	Pass
Electrostatic Properties	EN 1815	≤ 2kv
Staic Indentation	EN 433	≤ 0.1 mm
Usage Category	EN 685	23/42
Radiant Heat Suitability		Up to 28°C
Impact sound Reduction	ISO 10410	< 5dB
Resistance to Chemical	EN 423	Pass
Reaction to fire	EN 13501-1	Bfl – S1
	ASTM E84	
Inflammability	EN 13501-1	8.5
Smoke density	562.8 A	EN 13501-1
Smoke	STM E662	Pass
	ONORM B3800	Q1
Pentachlorophenol	BS 5666 part.6	Not detected
Emission of Formaldehyde	EN717-2	Not detected
Emission	CE 14041	Class A
Warranty	30 Residential	15 Commercial

The warranty covers manufacturing defects and premature wear in the event of normal use.

Installation & Warranty

All Plusfloor floors must be installed by a competent installer who will have the necessary skills and take individual site circumstances into account. Plusfloor's warranty will apply only to floors which have been installed by a competent flooring installer comparable to BS8201 in the UK or equivalent standard worldwide.

© This technical data sheet was written by Plusfloor, Carnforth Business Park, Oakwood Way, Carnforth, Lancashire, LA5 9FD. At the time of writing and publication of this folder, all information is specified correctly. The company reserves the right to change the specifications of this product at any time without prior notice to third parties.