







## ENDURO FERES

# Commercial strength polymer media filters

Thousands of installations over the last 35+ years bear testament to the quality and reliability of Poolrite "S" Series filters.

#### **Features**

- One piece seamless rotationally moulded tank designed for maximum strength
- Made from medium density polyethylene for strength & durability
- Clever designed dispersion inlet overdrain for smooth even flow of water into the filter tank
- Later underdrain design ensures maximum flow for fast and efficient backwashing which increases time between backwash cycles
- All non-corrosive construction suitable for all types of sanitation
- Australian design & manufacture

### **Warranty**

- 🕢 10 Year filter tank
- 1 Year on all other components




**Poolrite recommends using** 



#### **Dimensions**


#### E-5000






#### E-6000






#### E-8000





#### E-9000





**POOLRITE** 

## **Specifications**

MODEL	E-5000	E-6000	E-8000	E-9000
Filter Tank Diameter	522mm (20 in)	635mm (25 in)	770mm (30 in)	813mm (32 in)
Max Flow Rate (L/hr)	15,000	18,000	27,000	30,000
Diamond Kleen media M10 fine (kgs)	45	90	120	150
Diamond Kleen media M20 coarse (kgs)	30	45	45	60
Recommended Pump Model	SQI-400	SQI-500 / SQI-600	SQI-600	SQI-700

V2000 Multiport Valve

#### Featuring

- 50mm ports and large diameter valve for greater water flow and quieter operation
- Domed top cover to prevent debris building up around valve stem for easy operation and longevity
- 50mm plumbing unions allowing quick connection and simplified servicing with reducers to 40mm
- Over moulded gaskets to prevent spider gasket blow outs





