



MaxxAir have been manufacturing ventilation systems for the US RV market since 1988. Four fans are now exclusively available through Coast to Coast – the MaxxFan Plus and the MaxxFan Deluxe, both of which have a manual opening option or an electric opening option. They also feature a ceiling mounted control panel that is easy to use and read. RV ventilation has never been easier than with a MaxxFan.

## **FEATURES**

- Removable flyscreen simply twist the L-clamps and remove for cleaning!
- Installs into all standard 14" x 14" (356mm x 356mm) roof openings
- Powerful 10-speed fan motor
- The fan can run even if the lid is closed (select Ceiling Fan Mode) and can be used in "intake" and "exhaust" modes
- Provides for the extraction of over 25m³ of air per minute, keeping your RV cool and comfortable





#### MAXXFAN PLUS WITH THERMOSTAT AND MANUAL LIFT

**PART NUMBER:** 650-03010 **MODEL NUMBER: 4000KI** 

SPECIFICATIONS	
Amp Draw on High	2.6A
Amp Draw on Low	0.17A
Dimensions (closed)	461L x 420W x 97H (mm)
Dimensions (open):	461L x 420W x 311H (mm)
Installed Weight	4.1kg
Permanent Airflow	N/A
Roof Thickness	50mm (min) - 110mm (max)





### MAXXFAN PLUS WITH THERMOSTAT, POWER LIFT, RAIN SENSOR AND REMOTE

**PART NUMBER:** 650-03012 **MODEL NUMBER: 4540KI** 

SPECIFICATIONS	
Amp Draw on High	2.6A
Amp Draw on Low	0.17A
Dimensions (closed)	461L x 420W x 97H (mm)
Dimensions (open):	461L x 420W x 311H (mm)
Installed Weight	4.4kg
Permanent Airflow	N/A
Roof Thickness	50mm (min) - 110mm (max)





### MAXXFAN DELUXE WITH RAIN DOME, THERMOSTAT AND MANUAL LIFT

**PART NUMBER:** 650-03014 **MODEL NUMBER: 5100KI** 

SPECIFICATIONS	
Amp Draw on High	2.5A
Amp Draw on Low	0.16A
Dimensions (closed)	589L x 421W x 128H (mm)
Dimensions (open):	589L x 421W x 230H (mm)
Installed Weight	5.4kg
Permanent Airflow	82cm <sup>2</sup>
Roof Thickness	25mm (min) – 90mm (max)





# MAXXFAN DELUXE WITH RAIN DOME, THERMOSTAT, POWER LIFT AND REMOTE

**PART NUMBER:** 650-03016 **MODEL NUMBER:** 7000KI

SPECIFICATIONS	
Amp Draw on High	2.5A
Amp Draw on Low	0.16A
Dimensions (closed)	589L x 421W x 128H (mm)
Dimensions (open):	589L x 421W x 230H (mm)
Installed Weight	5.4kg
Permanent Airflow	82cm <sup>2</sup>
Roof Thickness	25mm (min) - 90mm (max)





DISTRIBUTED IN AUSTRALIA AND NEW ZEALAND BY:



coastrv.com.au | coastrv.co.nz Specifications are correct at time of printing and are subject to change without notice. DEALER / SUPPLIER