



**Catalogue**  
FOOD SERVICE  
**Chapter**  
DISHWASHING

**Specific model**  
CO-502 B DD 220-240V 1N 60Hz

19083235

08/11/2021

**DENOMINATION:**

Front loading dishwasher with electronic control, built-in drain pump and detergent doser 60 Hz

**DESCRIPTION :**

- Front-loading dishwashers - EVO Generation.
- Constructed in stainless steel.
- Whole body with double wall.
- Counterbalanced door with stainless steel hinges and double spring.
- Furniture which allows the machine to be positioned under 850 mm high work surfaces.
- Double rotating wash and rinse system, top and bottom, in stainless steel.
- Rounded tank to facilitate washing and drainage.
- Stainless steel armoured heating elements in the wash tank and rinse boiler.
- Useful internal height of 380 mm. Accepts GN 1/1 trays.
- Thermostatic control of temperatures (wash, 60°C, and rinse, 85°C).
- 600 W wash pump with SOFT-START.
- Boiler with capacity of 7 litres.
- Water consumption per 2.4 litre cycle.
- Rinse aid doser incorporated.
- Magnetic safety stop switch in door opening.
- Safety thermostat
- Model for 500 x 500 mm baskets.
- Model with electronic control and display of temperature, functions and errors.
- Electronic programmer with help system for technical service.
- 90s, 120s y 180s wash cycles.
- Theoretical maximum production of 40 baskets/hour.
- Tank with volume of 20 litres, with 2.8 kW heating element.
- Boiler with 5.6 kW heating element.
- Single-phase Multipower installation, with heating in the boiler which can be selected at time of installation, either 2,8 / 3,7 kW.
- Multi-voltage: Allows the machine to be connected to a single-phase or three-phase voltage network. (230 1N~/230 3~/400V 3N~).
- Thermal stop system which guarantees a rinse temperature of 85°C.
- Standard factory setting disabled.
- Tray-filter in the wash tank.
- IPX4 anti-humidity protection.
- Model with highly resistant control buttons.
- Built-in drain pump - power 35 W - drainage cycle
- Built-in detergent doser

**POSSIBLE OPTIONS :**


- Electric transformation to marine version (440V 3~ 60 Hz.)

**POSSIBLE ACCESSORIES :**

- STANDS
- VARIOUS KITS
- BASKETS FOR DISHWASHERS
- BASKETS FOR GLASSES
- WATER SOFTENERS

**SUPPLIED ACCESSORIES:**

**DIMENSIONS**



X Width	600 mm	X Gross width	660 mm
Y Depth	600 mm	Y Gross depth	745 mm
Z Height	830 mm	Z Gross height	1030 mm
Net Weight	67,0 kg	Gross Weight	82,0 kg
Net volume	0,299 m3	Gross volume	0,506 m3

**ELECTRICITY TECHNICAL SPECIFICATIONS**

Engine power	0,60 kW
Electric power	3,400 kW
Amperage (A)	14,7 A
Heating power	2,80 kW
Voltage	220-240V - 1N
Electric frequency	60Hz

**WATER TECHNICAL SPECIFICATIONS**

Pressure	H2O: 200-400kPa(2-4bar)
Water max consumption	54,00 L/h

**CONNECTIONS TECHNICAL SPECIFICATIONS**

230 V three-phase wiring	3 X 2,5 + T - 25A
Single-phase 230V wiring	2X6 + T - 40 A
Three-phase +N 400V wiring	4X2,5 + T - 20 A
Drain 1 diameter	2"

**OTHERS**

Noise level	65,00 dB
-------------	----------





Catalogue  
**FOOD SERVICE**

Capítulo  
**DISHWASHING**

Modelo  
**CO-502 B DD 220-240V 1N 60Hz**

19083235

08/11/2021

- 19000484 Standard basket 1
- 19000487 Basket for 16/18 dishes 1
- 19000792 Cutlery container 2



Catalogue  
**FOOD SERVICE**

Capítulo  
**DISHWASHING**

Modelo  
**CO-502 B DD 220-240V 1N 60Hz**

19083235

08/11/2021

