


## Undercounter Freezer

## TECHNICAL DRAWING


• Stainless steel interior and exterior.


**PRODUCT FEATURES** 


- Programmable Digital controller and display.
- 6 x 1/1 Gastronorm adjustable shelves with rails
- Compact slide out refrigeration unit for quick maintenance.
- 2 years parts and labour warranty.
- Comes standard with 4 x 115mm lockable castors (not legs).
- Optional Adjustable legs 150 180mm (Sold separately).



(23)







## PRODUCT SPECIFICATION

Exterior	Stainless Steel,
	Galvanized Steel (Rear /Bottom)
Interior	Stainless Steel
Max Storage Capacity	412L
Temperature Control	Microprocessor controlled Adjustable from
	-25 to -7°C
Condenser	Fin & Tube type, Air Cooled
Outside Dimensions	1660mm (W) x 700mm (D) x 815mm (H)
Inside Dimensions	1290mm (W) x 527mm (D) x 588mm (H)
Refrigeration System	Forced Air Circulation
Weight Net/Gross (kg)	103/115
AC Supply Voltage	1 PHASE 220 - 240V 50Hz /10amp Plug
Amperage	Rated: 3.4A Starting: 14.8A
Refrigerant Charge	R134a
Operating Conditions	Ambient Temp.: 5-43°C
	Voltage Range: Rated Voltage ±6%



Descriptions and specifications are subject to change at any time, without notice. Illustrations for demonstration purposes.

Copyright © 2019 Hoshizaki Lancer Pty Ltd. All right reserved. E&OE Date: Sept 2020

