


PRODUCT FEATURES

- Stainless steel interior and exterior
- Split doors on Upright series.
- Programmable electronic controller and display.
- 2 years parts and labour warranty.
- Standard with 4 x shelves
- Comes standard with 4 x lockable (115 mm) castors (not legs).
- Optional Adjustable legs 150 180mm (Sold separately).




TECHNICAL DRAWING

PRODUCT SPECIFICATION



627)	Interior	Stainless Steel, ABS Plastic (Doors)
	Exterior	Stainless Steel,Galvanized Steel (Top, Rear, Bottom)
	Max Storage Capacity	569L
	Temperature Control	Microprocessor adjustable from -23°C to -7°C
	Evaporator	Fin & Tube type
	Outside Dimensions	700mm (W) x 800mm (D) x 2015mm(H)
	Inside Dimensions	596mm (W) x 646mm (D) x 1484mm(H)
	Refrigeration System	Forced Air Circulation
	Weight Net/ Gross (kg)	104/ 126
	AC Supply Voltage	1 phase 220 - 240V 50Hz /10amp Plug
	Amperage	Rated: 4.1A Starting: 8.5A
	Refrigerant	R404A
	Operating Conditions	Ambient Temp.: 5-43°C Voltage Range: Rated Voltage ±6%



INSTALLATION REQUIREMENTS

- Equipment should not be located in direct sunlight or next to sources of high heat.*
- Allow at least 50 cm clearance between the front panel air inlet/outlet and the wall or other equipment for proper air circulation.*

*Refer to manual for full installation & maintenance requirements.



For free 12 month extended warranty, register online within 4 weeks of purchase date.

hoshizaki.com.au









