



ITEM	Hoshizaki Reach-in Refrigerator
MODEL	HRE-70B-ALD-GN
POWER SUPPLY	1 Phase 220 - 240V 50Hz Capacity: 0.82kVA (3.60A)
AMPERAGE	Rated: 2.08A Starting: 8.2A
ELECTRIC CONSUMPTION	348W (Power Factor: 73%) (Except Drain Pan Heater 170W) Heater: 437W Defrost: 437W
HEAT REJECTION	535W
POWER CORD	2.3m (Plug with Earth Wire)
EFFECTIVE CAPACITY	630L
OUTSIDE DIMENSIONS	700mm(W) x 850mm(D) x 2015(-2045)mm(H)
INSIDE DIMENSIONS	596mm(W) x 676mm(D) x 1484mm(H)
EXTERIOR	Stainless Steel, Galvanized Steel(Rear, Bottom)
INTERIOR	Stainless Steel
INSULATION	Polyurethane Foam
INSULATION FOAM BLOWING AGENT	Cyclopentane
DOOR	Full stainless steel doors external and interior
REFRIGERATION SYSTEM	Forced Air Circulation
DEFROST SYSTEM	Heater
COMPRESSOR	Hermetic 215W(Motor Size)
CONDENSER	Fin and Tube type, Air-cooled
EVAPORATOR	Fin and Tube type
REFRIGERANT	R134a/160g
TEMPERATURE CONTROL	Microprocessor (Digital Temp. Indication) Adjustable from -6 to 12°C
DEFROST CONTROL	Microprocessor
ELECTRIC CIRCUIT PROTECTION	Earth Wire, Circuit Breaker
REFRIGERANT CIRCUIT PROTECTION	Motor Protector (Auto-reset)
CASTER	Urethane (76mm DIA, 115mm HIGH)
ACCESSORIES	SHELF 4 pcs.
WEIGHT	124kg (Gross 146kg)
PACKAGE	Carton (Wooden Pallet) 760mm(W) x 950mm(D) x 2040mm(H)
OPERATING CONDITIONS	Ambient Temperature: 5 - 43°C Voltage Range: Rated Voltage ±6%

*We reserve the right to make changes in specifications and design without prior notice.

1. Install the product properly in accordance with the instructions on location, water supply/drain connections and electrical connections stated in the instruction and installation manuals provided.
Allow 10mm extra space at the installation site to meet any installation requirements (additional spacing is also required for proper air flow and pipe connections).
2. The heat rejection is based on the reached pulldown temperature at ambient temperature of 43°C.
3. The drain tank may overflow if the door is opened frequently or under highly humid conditions in the rainy or summer season.
4. Product Code : R273-C713

SPECIFICATIONS
 DRAIN TANK LONG DOOR
 GN 2/1 DOOR LOCK
 D850

HOSHIZAKI REACH-IN REFRIGERATOR HRE-70B-ALD-GN

APPROVED NAGASE	CHECKED WANG	DESIGNED SHAN	DRAWN SHAN	SCALE 1/20	TRIGONOMETRY
*	*	△	*****	DATE 2019.10.25	DRAWING NO. D27534
APPROVED	DESIGNED	SYMBOL	DATE		SYMBOL △