



	WATER CONNECTION 3/4" GAS
	DRAINING Ø 24mm
	ELECTRICAL SUPPLY

(***) MIN 130-MAX 200

TECHNICAL DATA	STANDARD			
EXTERNAL DIMENSIONS				
width	720 mm			
depth	735 mm			
height	1445 / 1880 mm			
WEIGHT	100 kg			
VOLTAGE	400V 3N 50Hz			
POWER EQUIRED	10900 W			
WATER HARDNESS	2-8 °F			
INLET WATER PRESSURE	200 - 400 kPa			
CROCKERY DIMENSIONS				
plates diameter	410 mm			
trays max. dimension	GASTRONORM 1/1 (530x325)			
RACK DIMENSIONS	500 x 500 mm			
RACK EQUIPMENT	2 x plate basket - 1 x mesh basket - 1 x cutlery container			
WASHING CYCLES (secs)	1(50)	2(80)	3(120)	4(180)
WATER SUPPLY 55°C				
rack/h(*) ⁽¹⁾	72	45	30	20
WATER SUPPLY 10°C				
rack/h(*) ⁽¹⁾	31	31	30	20
WATER CONSUMPTION / CYCLE (water pressure 200kPa)	2.8 L			
BOILER CAPACITY	10 L			
BOILER HEATING ELEMENT	9000 W			
RINSING TEMPERATURE (SET)	85 °C			
TANK CAPACITY	30 L			
TANK HEATING ELEMENT	2700 W			
TANK TEMPERATURE (SET)	55 °C			
PUMP POWER	1120 W (500 L/min ^{***})			
DRAIN PUMP	25 W h max draining 0.8 m (40 L/min ^{***})			
NOISE	63.6±0.7 dB(A)			

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.