



	WATER CONNECTION 3/4" GAS
	DRAIN PIPE Ø 32mm
	ELECTRICAL SUPPLY

TECHNICAL DATA		STANDARD			
EXTERNAL DIMENSIONS					
width	990 mm				
depth	885 mm				
height	1790 / 2050 mm				
WEIGHT	221 kg				
VOLTAGE	400V 3N 50Hz				
POWER EQUIRED	13360 W				
WATER HARDNESS	2-8 °F				
INLET WATER PRESSURE	200 - 400 kPa				
CROCKERY DIMENSIONS					
max. tray height	645 mm				
RACK DIMENSIONS	850 x 725 mm				
RACK EQUIPMENT	1 x spatula basket - 1 x tray support - 1 x s/steel basket				
WASHING CYCLES (min)	1(3)	2(6)	3(9)	4(12)	
WATER SUPPLY 55°C					
rack/h ^(*) (1)	20	10	6	5	
WATER SUPPLY 10°C					
rack/h ^(*) (1)	20	10	6	5	
WATER CONSUMPTION / CYCLE	4.3 L				
BOILER CAPACITY	20 L				
BOILER HEATING ELEMENT	9000 W				
RINSING TEMPERATURE (SET)	85 °C				
TANK CAPACITY	78 L				
TANK HEATING ELEMENT	6000 W				
TANK TEMPERATURE (SET)	55 °C				
WASHING PUMP POWER	2180 W (810 L/min ^{***}) x 2				
RINSING PUMP POWER	250 W (150 L/min ^{***})				
DRAIN PUMP (optional)	190 W (120 L/min ^{***})				
NOISE	71.1 dB(A)				

(*) STANDARD THERMOSTOP

(***) MAXIMUM FLOW RATE

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.