



	WATER CONNECTION 3/4" GAS
	DRAINING PIPE Ø 24mm
	ELECTRICAL SUPPLY

TECHNICAL DATA	PARTIAL DRAINING				CLEAN WATER(**)	
EXTERNAL DIMENSIONS						
width	600 mm					
depth	610 mm					
height	850 mm					
WEIGHT	65 kg					
VOLTAGE	240V 50Hz					
POWER EQUIRED	3700 W					
WATER HARDNESS	2 - 8 °F					
INLET WATER PRESSURE	200 - 400 kPa					
CROCKERY DIMENSIONS						
plates diameter	340 mm					
dishes max. height	340 mm					
RACK DIMENSIONS	500 x 500 mm					
RACK EQUIPMENT	1 x plate basket - 1 x mesh basket - 1 x cutlery container					
WASHING CYCLES (secs)	1(90)	2(120)	3(180)	(***) 4(60)	5(180)	6(360)
WATER SUPPLY 55°C						
rack/h(*) ⁽¹⁾	40	30	20	60	20	10
WATER SUPPLY 10°C						
rack/h(*) ⁽¹⁾	20	20	20	25	9	9
WATER CONSUMPTION / CYCLE	2.5 L		2.5 L		7 L	
BOILER CAPACITY	14 L					
BOILER HEATING ELEMENT	2800 W		3050 W		3050 W	
RINSING TEMPERATURE (SET)	85 °C			70 °C		85 °C
TANK CAPACITY	10 L				7 L	
TANK HEATING ELEMENT	1100 W					
TANK TEMPERATURE (SET)	60 °C					
washing/rinsing PUMPS	650 / 250 W					
DRAIN PUMP	25 W h max draining 0.8 m					
NOISE	61.3±0.7 dB(A)					

(*) STANDARD THERMOSTOP

(**) TOTAL DRAINING EVERY CYCLE

(***) GLASSES

¹⁾ In case of cold water supply and/or continuous washing, the rinse-water heating process might take more time than usual, until the proper rinse temperature is reached. For this reason, the wash -cycle total timing might result longer than set.