


PRODUCT ADVANTAGES

- Minimum space requirement: Vertical or horizontal installation next or on top of a glass-/dishwasher
- Continuous treatment system providing demineralised water for top-quality wash results
- Prevents salt and limescale stains on dishes, glasses and cutlery
- Protects machine against limescale deposits
- Optimises the effectiveness of detergents
- Minimum operating costs at highest capacity
- Bypass function: washing operation of the dishwasher is always guaranteed
- Easy to operate with integrated display
- Fast and easy removal of the pre-filter

TECHNICAL DATA

| | |
|--------------------------------|-------------|
| Power supply | 230/50/1 |
| Weight (gross / net) | 20 kg |
| Maximum hardness | 35 °dH* |
| Max. conductivity supply water | 1,200 µS/cm |
| Supply capacity Continuously | 2 l/min |

* The installation must be performed according to ATS 5200.101. A back flow prevention for the raw water supply must be installed. A back flow prevention for the drain connection is part of the optional installation kit. From 10° dH ,we recommend installing an upstream water softening system to prevent the blockage of the membrane. Hard water reduces the permeate output and shortens the life of the membrane.

CONNECTIONS

| | |
|-------------------------------|----------------------|
| Power Cord 230 V | 2,000 mm |
| Raw water connection | R 3/4" |
| Concentrate drain hose | 1,800 mm ID21/OD28 |
| Pure water hose | 2,000 mm R 3/4" |
| Flow pressure | 1- 6 bar |
| Max. supply water temperature | 35 °C |

DIMENSIONAL DRAWING
