



## Main Features

- ♦ 10.4" XGA TFT LCD monitor
- ♦ Aluminum die-casting and fanless design
- ♦ Built-in Intel® Atom™ x5-E3930 processor, 1.8GHz
- ♦ Automatic/manual brightness control
- ♦ Heater supported
- ♦ On screen F1 ~ F10 programmable function keys
- ♦ 5V/12V power supply for accessories
- ♦ Military standard for vibration and shock
- ♦ UPS Battery supported
- ♦ iButton and RFID for ID identification
- ♦ Wide range DC input from 9V~60V DC in
- ♦ Sunlight readable capability: 1,200nits LCD brightness

## Product Overview

VMC 3020, 10.4-inch all in one robust vehicle mount computer, is designed for the warehouses, logistic and material handling market. It implements the latest Intel® Atom™ x5-E3930 processor (codename Apollo Lake) and can work on Windows and Linux for different OS. markets. To work well in the special warehouse application, VMC 3020 specially designs powered I/O (up to 12V DC out) to power on printer, scanner... Besides, heater inside VMC 3020 can help forklift resume to work quickly when it stays in snow for a long time. Battery can assist system without stopping working if power suddenly drops down. 1,200 nits brightness is for sunlight readable purpose.

## Specifications

### LCD Panel

- ♦ 10.4-inch TFT LCD panel with LED backlight
- ♦ 1024 x 768 pixels (XGA)
- ♦ Brightness: 1200 cd/m<sup>2</sup> (typical)
- ♦ Viewing angle: 140° (H):120°(V)
- ♦ Contrast ratio: 500:1 (typical)

### Touch Screen Sensor

- ♦ 5-wire resistant touch
- ♦ Anti-glare coating surface
- ♦ Transmission rate: 81 ± 3%

### CPU & Chipset

- ♦ Intel® Atom™ x5-E3930 processor dual core 1.8GHz

### Memory

- ♦ One 204-pin DDR3L 1600MHz SO-DIMM slot (Default: 4GB)

### Expandable Storage

- ♦ 1 x CFast
- ♦ 1 x 2.5" SATA SSD bay

### Expansion

- ♦ 1 x half-size mini-PCIe socket (PCIe + USB) for WLAN option
- ♦ 1 x full-size mini-PCIe socket (USB) x 1 for WWAN option
- ♦ 1 x M.2 key-E (PCIe + SDIO + UART + USB) for WLAN option

### I/O Interface-Front

- ♦ 5 x on screen display buttons

Power on/off

Volume control (+/-)

Brightness control (+/-)

- ♦ Light sensor
- ♦ 4 x LED indicators (power/battery charging, WLAN, shift, storage)
- ♦ F1 ~ F10 programmable function keys
- ♦ 2 x Built-in 2W speakers


### I/O Interface-Lateral

- ♦ Right Side:
  - 1 x CFast card slot
  - System reset button
  - USB 2.0 host type A connector
- ♦ Left Side:
  - 1 x antenna for WWAN

### I/O Interface-Bottom

- ♦ 1 x Power Switch (ATX mode)
- ♦ Lockable power connector (power, ignition, ground)
- ♦ 2 x RS232 (full signals, RI, 0V, 5V/1.5A, 12V/1.5A)
- ♦ 1 x DB15
  - 1 x Isolated CAN 2.0B
  - 1 x iButton
  - 1 x RFID (12V/1A, 5V/1A, 4pin)
  - 1 x Optional RS232 Tx/Rx (share with GPS UART)
  - 2 x GPI
- Sink type: 5VDC TTL (default)

## Dimension Drawing



Source type: 3 ~ 28VDC

- 2 x GPO

Sink type: 5VDC TTL (default), max current: 20mA

Source type: 3 ~ 28VDC, max current: 150mA

- 1 x Powered USB (5V/1.5A, 12V/1.5A)
- 1 x USB Type A (5V/1A)
- 1 x Mic-in, 1 x Line-out
- 1 x Antenna for GPS

### I/O Interface-Top

- 2 x Antenna for Wi-Fi

### Mechanical

- Cooling system: Fanless
- Enclosure: Aluminum die castig
- Mounting: VESA 75/100 & desktop mounting
- Ingress protection: front panel IP65
- Dimension: 289.98mm (W) x 229.97mm (H) x 77.95mm (D), including battery
- Weight: 3kg, 6.61lb

### Power Management

- 9V~60V DC in (UPS: 12V, 24V, 36V and 48V)
- Reverse protection/over voltage protection/under voltage protection
- Ignition On/Off control & programmable On/Off delay timing
- Wake up by SMS, RTC and ignition

### Operating System

- Windows 10
- Linux: YOCTO (by request)

### Environment

- Operating temperatures: Ambient with air -30°C to 60°C
- Storage temperatures: -30°C to 70°C
- Relative humidity: 10% to 90% (non-condensing)
- Vibration
  - Operating: MIL-STD-810G, 514.6 Procedure 1, Category 4
  - Storage: MIL-STD-810G, 514.6 Procedure 1, Category 24
- Shock
  - Operating: MIL-STD-810G, Method 516.6, Procedure I, trucks and semi-trailers= 20g
  - Crash hazard: MIL-STD-810G, Method 516.6, Procedure V, ground equipment= 75g

### Standards/Certifications

- CE/FCC class B/E13

## Ordering Information

- **VMC 3020 (P/N: 10VC0320000X0)**  
10.4" Rugged Vehicle Mount Computer with Atom™ x5-E3930, Touch Screen and Front IP65 w/o Heater