
REOTEMP INSTRUMENTS Product Drawing



MS8 Seal - Pressure Gauge Assembly

| Part #: | MS8P2AF2XP21-SDDDASXDP |
|------------------|-------------------------------------|
| Gauge Data: | |
| Gauge Type: | 2.5" Dial, 304SS case, Bottom Mount |
| | |
| Pressure Range: | 0 - 300 psi |
| Case Material: | 304SS |
| Gauge Internals: | 316SS |
| Lens Material: | Clear Plastic |
| Case Fill: | None (Dry) |

| Seal Data: | |
|---------------------------|-------------------------------|
| Seal-to-Process Conn: | 1/2" NPT female |
| Seal-to-Gauge Connection: | Direct mount |
| Wetted material: | 316L SS |
| Diaphragm diameter: | 2.2 in. |
| Seal Fill Fluid: | Silicone DC200® |
| Flushing Connection: | None |
| Gasket Material: | None; all-welded construction |

| Operating Limits: | | min | max | |
|---|--|---------|----------|---|
| Ambient Temp: | | -40°F | 150°F | |
| Process Temp: | | -40°F | 400°F | |
| Max Working Pressure: | | 300 psi | | |
| Proof Pressure at 70°F: | | 390 psi | | |
| Max. Process Fluid Containment Pressure @ 70°F: | | | 3000 psi | i |

| Drawing Dimensions: | |
|---------------------|-------|
| Height "H": | 4 in. |

Data generated on: 11/10/2020 Revision: 6/1/2013 Rev. Date*:

*Revision date applies to all possible data: Individual drawings may not be affected. To obtain current revision, re-generate drawing at www.reotemp.com.

Made in U.S.A.

REOTEMP Instrument Corporation Consult factory for critical dimensions. Copyright REOTEMP Instruments **INSTRUMENTS**

San Diego, CA 92121 USA Phone: (858) 784-0710 Fax: (858) 784-0720

В CAGE CODE: 24793 NTS

JR

THIS DRAWING AND SPECIFICATIONS ARE THE PROPERTY OF REOTEMP INSTRUMENT CORP., AND ARE ISSUED IN STRICT CONFIDENCE AND SHALL NOT BE REPRODUCED. COPIED OR USED AS THE BASIS FOR MANUFACTURE OR SALE OF ITEMS DEPICTED HEREIN WITHOUT WRITTEN PERMISSION FROM REOTEMP INSTRUMENT CORP.

File Control MS8G-P2A MS8U-DDDA MS8L-XA MS8P-F2A

Notes: Dimensions are in inches (unless otherwise noted)

visit www.reotemp.com for attribution of trademarks.

1 OF 1