

OT40FT3



OT40FT3 SWITCH-DISCONNECTOR



General Information

| | |
|-----------------------|--|
| Extended Product Type | OT40FT3 |
| Product ID | 1SCA104940R1001 |
| EAN | 6417019390802 |
| Catalog Description | OT40FT3 SWITCH-DISCONNECTOR |
| Long Description | 3-pole, front operated, door mounted switch-diconnector / non-fusible disconnect switch with protected clamp terminals, handle is not included |

Popular Downloads

| | |
|-----------------------------------|--|
| Data Sheet, Technical Information | 1SCC301020C0201 |
| Instructions and Manuals | 1SCC301056M0006 |
| Mechanical Drawings | 1SCC301438F0001 1SCC301437F0001 OT16-40FT3.igs |

Dimensions

| | |
|----------------------------|--------|
| Product Net Width | 54 mm |
| Product Net Height | 43 mm |
| Product Net Depth / Length | 52 mm |
| Product Net Weight | 0.1 kg |

Technical

| | |
|--|---|
| Rated Operational Current AC-21A (I_e) | (380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A |
| Rated Operational Current AC-22A (I_e) | (380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A |
| Rated Operational Current AC-23A (I_e) | (380 ... 415 V) 23 A (500 V) 23 A (690 V) 12 A |
| Rated Operational Power AC-23A (P_e) | (220 ... 240 V) 5.5 kW (400 ... 415 V) 11 kW (500 V) 11 kW (690 V) 11 kW |
| Conventional Free-air Thermal Current (I_{th}) | q = 40 °C 40 A |
| Conventional Thermal Current (I_{the}) | Fully Enclosed 40 A |

| | |
|--|--|
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Rated Insulation Voltage (U_i) | acc. to IEC/EN 60664-1 750 V |
| Rated Operational Voltage | Main Circuit 750 V |
| Rated Short-Circuit Making Capacity (I_{cm}) | (690 V) 0.71 kA |
| Rated Short-time Withstand Current (I_{cw}) | for 1 s 0.5 kA |
| Power Loss | at Rated Operating Conditions per Pole 1.6 W |
| Pollution Degree | 3 |
| Handle Type | Handle and shaft not included |
| Switches Operating Mechanism | Mechanism on Top of the Switch |
| Distance Between Phases | Standard |
| Position of Line Terminals | Top In - Bottom Out Bottom In - Top Out |
| Operating Mode | Front operated |
| Standards | IEC 60947-3 / UL 508 / CSA C22.2 No. 14 |
| Special Functions | No |
| Mounting Type | Door mounting |
| Number of Poles | 3 |
| Cable Cross-Section | Cu 0.75...10 mm ² |
| Degree of Protection | Front IP20 |
| Terminal Type | Screw Terminals |
| Tightening Torque | acc. IEC 60947-1 0.8 N·m |
| Mechanical Durability | 20000 |

Technical UL/CSA

| | |
|----------------------------------|--|
| Maximum Operating Voltage UL/CSA | 600 V |
| Horsepower Rating UL/CSA | (110 ... 120 V AC) Single Phase 2 Hp (240 V AC) Single Phase 5 Hp (440 ... 480 V AC) Single Phase 10 Hp (550 ... 600 V AC) Single Phase 15 Hp (220 ... 240 V AC) Three Phase 10 Hp (440 ... 480 V AC) Three Phase 20 Hp (550 ... 600 V AC) Three Phase 25 Hp |
| Ampere Rating UL/CSA | 40 A |
| Tightening Torque UL/CSA | 7 in·lb |

Environmental

| | |
|---------------------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
| Environmental Information | 1SCC301183D0201 |

Certificates and Declarations (Document Number)

| | |
|--------------------------------|-----------------|
| Declaration of Conformity - CE | 1SCC301166D2703 |
| Environmental Information | 1SCC301183D0201 |
| Instructions and Manuals | 1SCC301056M0006 |
| RoHS Information | 1SCC301183D0202 |

Container Information

| | |
|-----------------------|---------|
| Package Level 1 Units | 1 piece |
|-----------------------|---------|

| | |
|--------------------------------|---------------|
| Package Level 1 Width | 59 mm |
| Package Level 1 Depth / Length | 60 mm |
| Package Level 1 Height | 58 mm |
| Package Level 1 Gross Weight | 0.11 kg |
| Package Level 1 EAN | 6417019390802 |

Classifications

| | |
|----------------------------|--|
| Object Classification Code | Q |
| ETIM 5 | EC000216 - Switch disconnecter |
| ETIM 6 | EC000216 - Switch disconnecter |
| ETIM 7 | EC000216 - Switch disconnecter |
| UNSPSC | 39122233 |
| WEEE Category | 5. Small Equipment (No External Dimension More Than 50 cm) |
| E-Number (Sweden) | 3170946 |

Categories

Low Voltage Products and Systems → Switches → Switch Disconnectors

