



This picture is for presentation purposes only, it does not represent actual product.

Description

DEKORON[®]/Unitherm[™] Series 2200 pre-insulated tubing is a thermally insulated transportation line suitable for steam, gas or liquid transport.

The energy-efficient design provides for nominal jacket surface temperature of 140°F (60°C) or lower at 90°F (32°C) ambient and wind speeds of 5mph, while transporting 450°F (232°C) saturated steam. Higher temperature designs for applications of up to 1000°F (537.8°C) are available in product Series 2210.

Features:

- Compact Design
- Low heat loss
- Low-maintenance
- Employee protection
- Easy to install
- Light, durable, easy to handle
- Consistent thermal characteristics

Applications:

- Steam supply lines
- Condensate return lines
- Gas transport lines
- Liquid transport lines
- Analyzer and instrument lines
- Small diameter process lines
- Impulse lines – D/P cells

Construction

1. (1) 1/2" O.D. x .035" Wall Type 316/316L ASTM A269 Welded Stainless Steel Process Tube
2. Non Wicking Inorganic Fibrous Glass Thermal Insulation
3. 105°C Black Flame Retardant DSJM Jacket

*** 100' Length Packaged In Box ***

DEKORON UNITHERM, LLC

1531 Commerce Creek Blvd. • Cape Coral, FL 33909

Toll Free: 800-633-5015






Telephone 239-995-8111 • Fax 239-995-8027

www.unithermcc.com



ISO 9001:2008 CERTIFIED

Pre-Insulated Product Catalog

Item Number : 2200-40A35-BX

MECHANICAL SPECIFICATIONS					
	Nominal OD Inches Millimeter	Min. Bending Radius Inches Centimeter	Working Pressure ¹ PSI Barg	Max. Continuous Length Foot Meter	Weight Lbs/FT Kgs/Me
	1.24 31.5	7.5 19.1	1950 134	100 30	40.00 59.51

¹ Working Pressure based on the MTR of this item in relation to the tables ASME B31.1-2001 and ASME B31.3-2001.

TEMPERATURE SPECIFICATIONS			Heat Loss Multipliers			
	Max Temp. Rating ¹ : °F °C	Minimum Install. Temp ² : °F °C	2200	2200	2200	2200
	450 232	-31 -35	1/4"	3/8"	1/2"	3/4"
			1.0	1.3	1.5	1.9

¹ Maximum Temperature Rating indicates the maximum temperature that the core of the bundle can withstand at the high ambient temperature of 80°F(26°C). Temperatures in excess of this rating may result in deterioration of the components. It does not represent maintenance temperature or rating of components distant from the core.

² Minimum Installation Temperature relates to the brittleness of this item's jacket material, during installation.

	Low	High
PVC	-36°F/-38°C	221°F/105°C
DSJM	-50°F/-45°C	221°F/105°C
TPU	-45°F/-43°C	212°F/100°C
TPE	-50°F/-45°C	257°F/125°C
PE	-76°F/-60°C	158°F/70°C

Recommended Accessories



Unicut[™] Bundle Jacket Cutter

End Sealant

End-Boots

Seal Patch Kits

Cable Entry Seals

Bundle Bender

Assigned accessories to item:

*BOOT-1 *SEAL 1.60 *1548-10000 / 1540-20000 *1535-02120

The information contained in this document is presented in good faith and believed to be reliable and accurate. However, because testing conditions may vary or information that may be provided in whole or in part by others may be beyond our control. No warranty expressed, implied or given. Dekoron Unitherm, LLC can assume no liability for results obtained or damages incurred through the application of the information presented.

DEKORON UNITHERM, LLC

1531 Commerce Creek Blvd. • Cape Coral, FL 33909

Toll Free: 800-633-5015

Telephone 239-995-8111 • Fax 239-995-8027

www.unithermcc.com

Item: 2200-40A35-BX

Revision: 20180328SP

ISO 9001:2008 CERTIFIED

Page: 2 OF 2