

## [ SELECTION TABLES. ] Load Center Accessories

### PowerMark Gold Main Circuit Breaker Kits

- For use with 125A PowerMark Gold load centers
- 22kAIC RMS symmetrical
- Includes mounting base
- For bottom feed, also purchase TRL22B door handle

Main Breaker Rating	Cat. No.	
	Main Breaker Kit	Description
100A	THQMH100CP	THQMH000 kit plus appropriate
125A	THQMH125CP	THHQL breaker
—	THQMH000	Order appropriate THQL <sup>①</sup> or THHQL breakers separately



THQMH100CP

① 10 kAIC

### Equipment Ground Kits

#### PowerMark Plus Equipment Ground Kits

Number of Terminals			Cat. No.	Std. Pkg
Small 14-8 Cu, 12-8 Al	Large 14-4 Cu, 12-4 Al	Other AWG/kcmil Cu/Al		
4	3	—	TGL1 <sup>①</sup>	20
7	—	—	TGL3 <sup>①</sup>	
11	3	—	TGL2 <sup>②</sup>	
14	—	—	TGL4 <sup>②</sup>	
10	2	(1) 14-2	TGL8 <sup>②</sup>	
—	—	(1) 6-2/0	TGL20 <sup>③</sup>	1
—	—	(3) 10-1/0	TNG3 <sup>④</sup>	
—	—	(6) 10/1-0	TNG6 <sup>④</sup>	

- ① TGL1 and TGL3 mount interchangeably.
- ② TGL2, TGL4 and TGL8 mount interchangeably.
- ③ Add-on equipment ground lug (for use on any TGL kit).
- ④ Suitable only for 400 and 600 amp devices.

#### PowerMark Gold and Three Phase PowerMark Plus Equipment Ground & Isolated Ground Bus Bar

Description (4-14 CU/10-12 Al Wire Ranges Per Hole, Solid or Stranded)	Cat. No.	Std. Pkg.
12-hole Ground	TGK12	1
24-hole Ground	TGK24	
32-hole Ground	TGK32	
42-hole Ground	TGK42	
Isolated Ground Bus Bar Kit (Order with TGK Equipment Ground Kits)	TGKIS	



TGL2



TGK12 with TGKIS



TGK12

### Neutral Kits

#### PowerMark Plus Neutral Kits

Wire Size AWG/kcmil Cu/Al	Cat. No.	Std. Pkg.
(5) 14-1/0	TNLK1 <sup>①</sup>	1
(3) 1-300	TNLK2 <sup>①</sup>	
(1) 6-2/0 Cu/Al	286A8894G1 <sup>②</sup>	
(1) 1-300 Cu or 2/0-300 Al	192A7663G13 <sup>②</sup>	

- ① Suitable only for 400 and 600 amp devices.
- ② Add-on neutral lug kit for 100-200 amp load centers.

#### PowerMark Gold Neutral and Neutral Ground Kits

Description	Wire Size	Cat. No.	Std. Pkg.
Neutral	6-1 Cu/Al	TNLK12	1
Neutral	6-2/0 Cu/Al	TNLK20	
Neutral	6-250 Cu/Al	TNLK250	
Neutral/Ground	6-2/0 Cu/Al	TLK20	
Neutral/Ground	6-250 Cu/Al	TLK250	



TNLK1



TLK20 shown attached to neutral/ground bar



TLK250 shown attached to neutral/ground bar



TNLK20



TNLK250




TLK250



TLK250

### Main Lug Kits

Load Center Type	Wire Size AWG/kcmil Cu/Al	Ampere Rating	Cat. No.
PowerMark Plus	2-3/0	150	THLK150
	1-250	200	THLK200
PowerMark Gold	6-2/0	125	TMLK125
	6-250	200	TMLK200
	6-300	225	TMLK225



THLK200



TMLK200