



Section 1 – IDENTIFICATION OF THE MATERIAL AND SUPPLIER

Product Name:	Dry Lube PTFE Aerosol 400 ml
Product Code:	7484
Uses:	Lubricant Dry Film PTFE Lubricant Aerosol
Company:	Chemz Limited
Address:	80 Rangitane Place
	Whakatu, Hastings
Telephone:	+64 6 877 9690
Email:	info@chemz.co.nz
Emergency Number 24 hr:	0800 764 766 (0800 POISON) National Poison Centre

Section 2 – HAZARDS IDENTIFICATION

Classification of the product

Considered a hazardous substance according to the Hazardous Substance (Minimum Degrees of Hazard) Regulations NZ. Classified as a dangerous goods for transport purposes.

GHS Classifications:

GHS Classifications:	HSNO Classifications:	
Aerosol Category 1	2.1.2A	Flammable aerosol
Eye irritation Category 2	6.4A	Irritating to the eye



Signal Words: Danger

Hazard Statements

H222 Extremely flammable aerosol

H229 Pressurised container: May burst if heated

H319 May cause serious eye irritation

Section 3 – COMPOSITION INFORMATION ON INGREDIENTS

Hazardous Ingredients	CAS No.	Proportion, % m/m
2 -Propanol	67-63-0	10 - 30
Polytetrafluoroethylene	65530-85-0	1 - 10
LPG (butane, propane)	68476-85-7	> 60

Section 4 – FIRST AID MEASURES

If medical advice is needed, have product container or label at hand.

If exposed or if you feel unwell: Call a POISON CENTRE or doctor.

Eye contact:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice.





Inhalation:	IF INHALED: If breathing is difficult, remove to fresh air and keep at rest in a position comfortable for breathing. If experiencing respiratory symptoms: Call a POISON CENTRE or doctor.
Skin contact:	IF ON SKIN: Wash with plenty of soap and water. If skin irritation or rash occurs: Get medical advice.
Ingestion:	Not considered a normal route of entry. IF SWALLOWED: Immediately call a POISON CENTRE or doctor. Do NOT induce vomiting. Obtain immediate medical attention.
Notes to physician:	Treat symptomatically and supportively. No specific antidote.

Section 5 – FIRE-FIGHTING MEASURES

General fire hazards:	Pressurised container, extremely flammable aerosol.
Specific hazards:	Containers can build up pressure if exposed to heat and/or fire and may explode. Vapours may form an explosive mixture with air. Vapours can travel to a source of ignition and flash back. Contents may float and be re-ignited on surface water.
Further advice:	On burning may emit toxic fumes including those of carbon monoxide and carbon dioxide. Fire fighters to wear self-contained breathing apparatus if risk of exposure to products of combustion.
Extinguishing media:	Use water spray, fog, or foam. Use water spray to cool fire-exposed containers. Water may be ineffective. Do not discharge extinguishing waters into the aquatic environment. Do NOT use straight streams of water.
Protective equipment:	Firefighters must use standard protective equipment including flame retardant coat, helmet with face shield, gloves, rubber boots, and in enclosed spaces, SCBA.
Firefighting instructions:	In the event of fire, cool containers with water spray to prevent vapour pressure build up. Move containers from fire area if you can do so without risk. Runoff can cause environmental damage.
Hazchem Code:	2YE

Section 6 – ACCIDENTAL RELEASE MEASURES

Minor spills:	Clean up all spills immediately. Remove all sources of ignition. If safe to do, damaged cans should be placed in a container outdoors, away from all ignition sources, until pressure has dissipated. Undamaged cans should be gathered and stowed safely. Provide ventilation. Wash with water.
Major spills:	Evacuate the spill area. Call the Fire Brigade. Remove all sources of ignition. If safe to do so, prevent spillage from entering drains or water courses. If material enters drains, advise emergency services. Use absorbent (soil, sand or other inert material). Collect and seal in properly labeled containers for disposal.

Section 7 – HANDLING AND STORAGE

Handling Precautions:Read product label before use. Keep out of reach of children. Obtain special instructions before use. Do
not handle until all safety precautions have been read and understood.This product is highly flammable. Keep away from heat and open flames. Do not spray on an open flame or
other ignition source. Pressurised container: Do not pierce or burn, even after use. No smoking. Beware:
Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.
Use outdoors or in a well-ventilated area. Avoid breathing spray or vapours. Wash hands with soap and
water after handling.Storage:Protect from sunlight. Do not expose to temperatures exceeding 50 °C. Store in a well ventilated, cool,
dry place. Keep away from heat, sparks, and flame. Store locked up.

Section 8 – EXPOSURE CONTROLS/PERSONAL PROTECTION

Exposure Limits:

No value assigned for product. Exposure standards for constituents (NZ WES);

Material	TWA, mg/m ³	STEL, mg/m ³
2-Propanol	1,200	-
LPG (Liquefied petroleum gas – butane, propane)	1800	-





Additional Information:	Wash hands before eating, drinking and smoking.
Engineering Controls:	No controls generally required when handling small quantities. Use with adequate ventilation.
	Larger quantities: General exhaust is adequate under normal operating conditions. Exhaust ventilation should be designed to prevent accumulation and recirculation in the workplace. Ventilation equipment and lighting should be explosion-resistant.
Protective Equipment:	General protective gloves are recommended. In an industrial environment: chemical protective gloves, safety glasses or chemical goggles are recommended. Wash contaminated clothing before reuse. Contaminated work clothing should not be allowed out of the workplace.
	In case of inadequate ventilation, wear respiratory protection. If TWA is exceeded, wear an approved respirator with a type A filter.

Section 9 – PHYSICAL AND CHEMICAL PROPERTIES

Physical state:	Clear, liquid spray with slight hydrocarbon odour.
pH:	Not applicable.
Vapour Density:	> 1 (Air =1)
Vapour Pressure, kPa:	300 - 600
Boiling Point, °C:	About 80
Melting Point, °C:	Not applicable.
Specific Gravity:	About 0.78
Flash Point, °C:	< 0 (propellant)
Explosion Limit, % v/v:	LEL 1.2% UEL 9.5%
Autoignition Temp, °C:	> 200
Solubility:	Partially miscible in water.

Section 10 – STABILITY AND REACTIVITY

Stability:

Stable under normal conditions of use. Not reactive. Avoid oxidisers. Avoid elevated temperatures.

Section 11 – TOXICOLOGICAL INFORMATION

Basis for Assessment:	Information given is based on product testing, and/or similar products, and/or components.
Acute Oral Toxicity:	LD_{50} estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).
Acute Dermal Toxicity:	LD_{50} estimated to be > 5,000 mg/kg (based on component mixture, excluding propellant).
Acute Inhalation Toxicity:	LC_{50} estimated to be > 20 mg/L, Rat 4 hour (based on component mixture).
	Beware: Deliberately sniffing or inhaling concentrated contents can be harmful or fatal.
Skin Irritation:	May cause slight skin irritation. Avoid contact with skin.
Eye Irritation:	May cause serious eye irritation. Avoid contact with eyes. Expected to be reversible in less than 7 days.
Sensitisation:	Not expected to be a contact or respiratory sensitiser.
Respiratory Irritation:	Inhalation of vapours or mists may cause irritation to the respiratory system.
Inhalation:	Inhalation may cause drowsiness or dizziness. Inhalation may cause narcotic effects.
Mutagenicity:	Not expected to be mutagenic.
Carcinogenicity:	Not expected to be carcinogenic.
Reproductive toxicity:	Not expected to be toxic.
Constitue Towner Construction	

Specific Target Organ Toxicity: Harmful to human target organs or systems (Single exposure)





	SALLIT DATA SILLI
STOT (Narcotic):	Prolonged inhalation of vapours may be narcotic and cause drowsiness or dizziness.
Repeated Dose Toxicity:	Repeated, prolonged exposure by inhalation may cause damage to organs.
Additional Information:	None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, OSHA or ACGIH as being carcinogens.
Section 12 – ECOTOXICITY	INFORMATION
Ecotoxicity:	Not expected to be ecotoxic.
Mobility:	Product is volatile and will rapidly evaporate to the air if released into water.
Persistence/degradability:	More volatile components expected to degrade in air. Low persistence, expected to rapidly degrade in environment.
Bioaccumulation Potential:	Not expected to bioaccumulate.
Section 13 – DISPOSAL CO	NSIDERATIONS
Material Disposal:	Product wastes should be disposed of in accordance with applicable regulations. Do not dispose into the environment, in drains or in water courses.
	Large quantities should be degassed by an aerosol recycler. Do not dispose of large quantities of pressurised aerosols in landfills. Incineration in an authorised facility is suggested.
Container Disposal:	Recycle empty container if possible or dispose in landfill. Product containers are also considered wastes of the same class of the contents and should be disposed of in accordance with applicable regulations.
Section 14 – TRANSPORT I	NFORMATION
Transport:	Classified as a Dangerous Good for transport purposes.
	Class 2.1 should not be loaded on the same vehicle as Classes 1, 3 (where both are in bulk), 4, 5, and 7. They may be loaded with Classes 3, 6, 8, 9, foodstuffs and foodstuff empties.
Proper Shipping Name:	Aerosols
UN Number:	1950
Dangerous Goods Class:	2.1
Transport Labels Required:	Class 2 Flammable (Land, Sea and Air)
	Land, Sea, Air
	PLANE AND
Subsidiary Risk:	Not applicable
Packing Group:	Not applicable
Marine Pollutant:	Yes
EMS Number	F-D, S-U (UN 1950 Flammable aerosols)
DG Segregation:	This product is classified as a Dangerous Goods. Consult the Land Transport Rule: Dangerous Goods 2005 and NZS 5433:2012 Transport of Dangerous Goods on Land for information.
Section 15 – REGULATORY	INFORMATION
Inventory Listing	NZIOC (New Zealand Inventory of Chemicals); All components of this product are listed.
SDS regulations	This Safety Data Sheet was prepared in accordance with the EPA Hazardous Substances (Safety Data Sheets) Notice July 2017.





HSR002515 Aerosols (Flammable) Group Standard 2020. Refer to <u>www.epa.govt.nz</u> for information on Controls. This substance is to be managed using the conditions specified in an applicable Group Standard.			
		ORMATION	
		Personal Protective Equipment Guidelines: The recommendation for protective equipment contained is provided as a guide only. Factors such as method of application, working environment, quantity used, product concentration and the availability of engineering controls should be considered before final selection of personal protective equipment is made.	
depend on control mea prepare a re	cts from Exposure: It should be noted that the effects from exposure to this product will several factors including: frequency and duration of use; quantity used; effectiveness of asures; protective equipment used and method of application. Given that it is impractical to eport which would encompass all possible scenarios, it is anticipated that users will assess the oply control methods where appropriate.		
CAS	Chemical Abstract Service number		
EMS	Emergency Response Procedures for Ships Carrying Dangerous Goods		
EPA	Environmental Protection Agency		
GHS	Globally Harmonized System		
IARC	International Agency for Research on Cancer		
IATA	International Air Transport Association		
IMDG	International Maritime Dangerous Goods		
LC ₅₀	Lethal Concentration, 50% / Median Lethal Concentration		
LD ₅₀	Lethal Dose, 50% / Median Lethal Dose		
LEL	Lower Explosion Limit		
mg/m³	Milligrams per Cubic Metre		
NZIoC	New Zealand Inventory of Chemicals		
N.O.S.	Not otherwise specified		
OEL	Occupational Exposure Limit		
PEL	Permissible Exposure Limit		
STEL	Short-Term Exposure Limit		
STOT-RE	Specific target organ toxicity (repeated exposure)		
	Specific target organ toxicity (single exposure)		
	Threshold Limit Value		
	Time Weighted Average		
	Upper Explosion Limit		
	Refer to wy This substa DRMATION Personal Pr provided as product cor selection of Health Effer depend on control mea prepare a ra risks and ap CAS EMS EPA GHS IARC IATA IMDG LC ₅₀ LD ₅₀ LEL mg/m ³ NZIOC N.O.S. OEL PEL STEL		

This SDS summarises our best knowledge of the health and safety hazard information. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. Since we cannot control the conditions under which the product may be used, each user must review this SDS in the context of how the user intends to use the product. End of sds.