

Issue date: 12/09/2023

Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

Section 1. Identification of the substance or the mixture and of the supplier

1.1 Product Identifier

Product identifier: CRACKLING LOG FIRE FRAGRANCE 903787 (Contains:(1S,2R,5S,7R,8R)-8-METHOXY-

2,6,6,8-TETRAMETHYLTRICYCLO[5.3.1.0^{1,5}]UNDECANE, 4-TERT-BUTYLCYCLOHEXYL

ACETATE, EUGENOL, TETRAMETHYL ACETYLOCTAHYDRONAPHTHALENES)

Other identifiers: None

1.2 Relevant identified uses of the substance of mixture and uses advised against

Product uses: Fragrances

1.3 Details of the supplier of the safety data sheet

Company name: Bomar Ltd
Company address: Sea Road

Kilcoole Co. Wicklow A63 TW67

(Office hours: Monday to Friday 09.00 to 17.30

Contact: Regulatory Affairs
E-Mail address: info@bomar.ie
Company phone: +353 1 2875110

1.4 Emergency telephone number

Emergency phone: Outside Office Hours: +353 87 2188113

Section 2. Hazards identification

2.1 Classification of the substance or mixture

Classification under Regulation (EC) No 1272/2008

Class and category of Sensitization - Skin Category 1

danger: Hazardous to the Aquatic Environment - Acute Hazard Category 1

Hazardous to the Aquatic Environment - Long-term Hazard Category 1

H317, May cause an allergic skin reaction.

H410, Very toxic to aquatic life with long lasting effects.

2.2 Label elements

Classification under Regulation (EC) No 1272/2008

Signal word: Warning

Hazard statements: H317, May cause an allergic skin reaction.

H410, Very toxic to aquatic life with long lasting effects.



Issue date: 12/09/2023

Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

Supplemental Information:

EUH208, Contains ALPHA-ISOMETHYL IONONE, ALPHA-PINENES, BETA-CARYOPHYLLENE, METHYL ATRATATE. May produce an allergic reaction.

Precautionary statements:

P261, Avoid breathing vapour or dust.

P272, Contaminated work clothing should not be allowed out of the workplace.

P273. Avoid release to the environment.

P280, Wear protective gloves/eye protection/face protection. P302/352, IF ON SKIN: Wash with plenty of soap and water.

P333/313, If skin irritation or rash occurs: Get medical advice/attention.

P363, Wash contaminated clothing before reuse.

P391, Collect spillage.

P501, Dispose of contents/container to approved disposal site, in accordance with local

regulations.





Pictograms:

2.3 Other hazards

Other hazards: Sensitisers declared on a CLP

Hazard Label:

ALPHA-ISOMETHYL IONONE, ALPHA-PINENES, BETA-

CARYOPHYLLENE, METHYL ATRATATE

Hydrocarbon Concentration %: 8.314%

Section 3. Composition / information on ingredients

3.2 Mixtures

Contains:

Name	CAS	EC	REACH Registration No.	%	Classification for (CLP) 1272/2008	Specific Conc. Limits, M-factors and ATEs
4-TERT- BUTYLCYCLOHEXYL ACETATE	32210-23-4	250-954-9	01-2119976286-24-xxxx	20-<50%	ISS 1B:H317 -	oral: ATE = 3370 mg/kg bw
AMYL SALICYLATE	2050-08-0	218-080-2		5-<10%	- ,	oral: ATE = 2000 mg/kg bw
CEDROL	77-53-2	201-035-6		1-<5%	EH C2;H411,-	
ALPHA-CEDRENE	469-61-4	207-418-4		1-<5%	SCI 2-AH 1-EH A1-EH C1;H304-H315-H410,-	M = 10-M = 10
2-METHYLBUTYL SALICYLATE	51115-63-0	256-972-3		1-<5%	- ,	oral: ATE = 1406 mg/kg bw
(1S,2R,5S,7R,8R)-8- METHOXY-2,6,6,8- TETRAMETHYLTRICY CLO[5.3.1.0^{1,5}] UNDECANE	67874-81-1	267-510-5		1-<5%	SS 1B-EH A1-EH C1; H317-H410,-	





Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

ACETYLOCTAHYDRON	54464-57-2, 54464-59-4, 68155-66-8, 68155-67-9	259-174-3, 259-175-9, 268-978-3, 268-979-9, 915-730-3	01-2119489989-04-xxxx	1-<5%	SCI 2-SS 1B-EH C2; H315-H317-H411,-	
EUGENOL	97-53-0	202-589-1		1-<5%	EDI 2-SS 1B;H317- H319,-	oral: ATE = 2500 mg/kg bw
BETA CEDRENE	546-28-1	208-898-8		0.1-<1%	AH 1-EH A1-EH C1; H304-H410,-	
ALPHA-ISOMETHYL IONONE	127-51-5	204-846-3		0.1-<1%	SS 1B-EH C2;H317- H411,-	
METHYL ATRATATE	4707-47-5	225-193-0		0.1-<1%	SS 1B;H317,-	
BETA- CARYOPHYLLENE	87-44-5	201-746-1		0.1-<1%	SS 1B-AH 1;H304- H317,-	
ALPHA-PINENES	80-56-8	201-291-9		0.1-<1%	FL 3-ATO 4-SCI 2-SS 1B-AH 1-EH A1-EH C1;H226-H302-H304- H315-H317-H410,-	oral: ATE = 500 mg/kg bw

Substances with Community workplace exposure limits:

Name	CAS	EC	REACH Registration No.		Classification for (CLP) 1272/2008	
DIETHYL PHTHALATE	84-66-2	201-550-6	01-2119486682-27-xxxx	20-<50%	-;-,-	
PROPYLENE GLYCOL	57-55-6	200-338-0	01-2119456809-23-xxxx	0.1-<1%	-;-,-	

Substances that are endocrine disruptors according to Regulation (EU) 2017/2100 or Regulation (EU) 2018/605, greater than 0.1%:

Not Applicable

Substances that are persistent, bioaccumulative and toxic or very persistent and very bioaccumulative, greater than 0.1%:

Not Applicable

Section 4. First-aid measures

4.1 Description of first aid measures

Inhalation: Remove from exposure site to fresh air, keep at rest, and obtain medical attention.

Eye exposure: Flush immediately with water for at least 15 minutes. Contact physician if symptoms persist.

Skin exposure: IF ON SKIN: Wash with plenty of soap and water. **Ingestion:** Rinse mouth with water and obtain medical attention.

4.2 Most important symptoms and effects, both acute and delayed

May cause an allergic skin reaction.

4.3 Indication of any immediate medical attention and special treatment needed

None expected, see Section 4.1 for further information.



Issue date: 12/09/2023

Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

Section 5: Firefighting measures

5.1 Extinguishing media

Suitable media: Carbon dioxide, Dry chemical, Foam.

5.2 Special hazards arising from the substance or mixture

In case of fire, may be liberated: Carbon monoxide, Unidentified organic compounds.

5.3 Advice for fire fighters:

In case of insufficient ventilation, wear suitable respiratory equipment.

Section 6. Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures:

Avoid inhalation. Avoid contact with skin and eyes. See protective measures under Section 7 and 8.

6.2 Environmental precautions:

Keep away from drains, surface and ground water, and soil.

6.3 Methods and material for containment and cleaning up:

Remove ignition sources. Provide adequate ventilation. Avoid excessive inhalation of vapours. Contain spillage immediately by use of sand or inert powder. Dispose of according to local regulations.

6.4 Reference to other sections:

Also refer to sections 8 and 13.

Section 7. Handling and storage

7.1 Precautions for safe handling:

Keep away from heat, sparks, open flames and hot surfaces. - No smoking. Use personal protective equipment as required. Use in accordance with good manufacturing and industrial hygiene practices. Use in areas with adequate ventilation Do not eat, drink or smoke when using this product.

7.2 Conditions for safe storage, including any incompatibilities:

Store in a well-ventilated place. Keep container tightly closed. Keep cool. Ground/bond container and receiving equipment. Use explosion-proof electrical, ventilating and lighting equipment. Use only non-sparking tools. Take precautionary measures against static discharge.

7.3 Specific end use(s):

Fragrances: Use in accordance with good manufacturing and industrial hygiene practices.





Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

Section 8. Exposure controls/personal protection

8.1 Control parameters

Workplace exposure limits:

Ingredient	CAS	EC	Description	Value
DIETHYL PHTHALATE	84-66-2	201-550-6	UK Long-term exposure limit (8-hour TWA) (mg/m3)	5 mg/m³
DIETRYL PHTHALATE	04-00-2		UK Short-term exposure limit (15-minute) (mg/m3)	10 mg/m³
PROPYLENE GLYCOL	57-55-6	200-338-0	UK Long-term exposure limit (8-hour TWA) (ppm)	150 ppm
PROFILENE GLYCOL	107-00-0		UK Long-term exposure limit (8-hour TWA) (mg/m3)	474 mg/m³

8.2 Exposure Controls

Eye / Skin Protection

Wear protective gloves/eye protection/face protection

Respiratory Protection

Ensure adequate and ongoing ventilation is maintained in order to prevent build up of excessive vapour and to ensure occupational exposure limits are adhered to. If appropriate, and depending on your patterns and volumes of use, the following engineering controls may be required as additional protective measures: a) Isolate mixing rooms and other areas where this material is used or openly handled. Maintain these areas under negative air pressure relative to the rest of the plant. b) Employ the use of Personal protective equipment - an approved, properly fitted respirator with organic vapour cartridges or canisters and particulate filters. c) Use local exhaust ventilation around open tanks and other open sources of potential exposures in order to avoid excessive inhalation, including places where this material is openly weighed or measured. In addition, use general dilution ventilation of the work area to eliminate or reduce possible worker exposures. d) Use closed systems for transferring and processing this material.

Also refer to Sections 2 and 7.

Section 9. Physical and chemical properties

9.1 Information on basic physical and chemical properties

Physical State/Colour: Clear pale yellow liquid

Odour: Not determined
Odour threshold: Not determined
Melting point/freezing point: Not determined
Boiling point or initial boiling point and boiling
Not determined

range:

Flammability: Not determined

Lower and upper explosion limit: Not determined

Flash point: > 100 °C

Auto-ignition temperature: Not determined



Issue date: 12/09/2023

Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

Decomposition temperature:

pH:

Not determined

Kinematic viscosity:

Not determined

Solubility:

Not determined

Not determined

Not determined

Not determined

value):

Vapour pressure: 0.03138564 mmHg

Density and/or relative density: 1.0200

Relative vapour density: Not determined Particle characteristics: Not determined

9.2 Other information: None available

Section 10. Stability and reactivity

10.1 Reactivity:

Presents no significant reactivity hazard, by itself or in contact with water.

10.2 Chemical stability:

Good stability under normal storage conditions.

10.3 Possibility of hazardous reactions:

Not expected under normal conditions of use.

10.4 Conditions to avoid:

Avoid extreme heat.

10.5 Incompatible materials:

Avoid contact with strong acids, alkalis or oxidising agents.

10.6 Hazardous decomposition products:

Not expected.

Section 11. Toxicological information

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008

This mixture has not been tested as a whole for health effects. The health effects have been calculated using the methods outlined in Regulation (EC) No 1272/2008 (CLP).

Acute Toxicity: Based on available data the classification criteria are not met.

Acute Toxicity Oral >5000

Acute Toxicity Dermal Not Applicable
Acute Toxicity Inhalation Not Available

Skin corrosion/irritation:Based on available data the classification criteria are not met. **Serious eye damage/irritation:**Based on available data the classification criteria are not met.

Respiratory or skin sensitisation: Sensitization - Skin Category 1

Germ cell mutagenicity:Based on available data the classification criteria are not met.



Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

BOMAR

Carcinogenicity:Based on available data the classification criteria are not met.Reproductive toxicity:Based on available data the classification criteria are not met.STOT-single exposure:Based on available data the classification criteria are not met.STOT-repeated exposure:Based on available data the classification criteria are not met.Aspiration hazard:Based on available data the classification criteria are not met.

Information about hazardous ingredients in the mixture

Ingredient	CAS	EC	LD50/ATE Oral	LD50/ATE Dermal	LC50/ATE Inhalation	LC50 Route
2-METHYLBUTYL SALICYLATE	51115-63-0	256-972-3	1406	Not available	INOt available	Not available
AMYL SALICYLATE	2050-08-0	218-080-2	2000	Not available	Not available	Not available

Refer to Sections 2 and 3 for additional information.

11.2 Information on other hazards

Not Applicable

Section 12. Ecological information

12.1 Toxicity:

Very toxic to aquatic life with long lasting effects.

12.2 Persistence and degradability:Not available12.3 Bioaccumulative potential:Not available12.4 Mobility in soil:Not available

12.5 Results of PBT and vPvB assessment:

This substance does not meet the PBT/vPvB criteria of REACH, annex XIII.

12.6 Endocrine disrupting properties: Not Applicable **12.7 Other adverse effects:** Not available

Section 13. Disposal considerations

13.1 Waste treatment methods:

Dispose of in accordance with local regulations. Avoid disposing into drainage systems and into the environment. Empty containers should be taken to an approved waste handling site for recycling or disposal.

Section 14. Transport information

	14.1 UN number or ID number:	and other other other states	14.3 Transport hazard class (es):	Sub Risk:	14.4 Packing Group:
UN Model Regulations	UN3082	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALPHA- CEDRENE, AMYL SALICYLATE)	9	-	III



Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

IMDG	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALPHA- CEDRENE, AMYL SALICYLATE) MARINE POLLUTANT	9	-	III
ADR,RID,ADN	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALPHA- CEDRENE, AMYL SALICYLATE)	9	-	III
ICAO TI	ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S. (ALPHA- CEDRENE, AMYL SALICYLATE)	9	-	III

14.5 Environmental hazards: This is classified as an environmentally hazardous substance under the UN

Model Regulations. This is classified as a Marine Pollutant under the IMDG

Code.

14.6 Special precautions for user: None additional

14.7 Maritime transport in bulk according to IMO instruments:

Not applicable

Section 15. Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture None additional

15.2 Chemical Safety Assessment

A Chemical Safety Assessment has not been carried out for this product.

Section 16. Other information

Concentration % Limits: SS 1=3.65% EH A1=55.01% EH C1=55.01% EH C2=5.41% EH C3=0.

54050314% EH C4=46.71%

Total Fractional Values: SS 1=27.40 EH A1=1.82 EH C1=1.82 EH C2=18.50 EH C3=185.01 EH

C4=2.14

Key to revisions:

SECTION 3: Composition/information on ingredients

Key to abbreviations:

Abbreviation	Meaning
AH 1	Aspiration Hazard Category 1
ATO 4	Acute Toxicity - Oral Category 4
EDI 2	Eye Damage / Irritation Category 2
EH A1	Hazardous to the Aquatic Environment - Acute Hazard Category 1
EH C1	Hazardous to the Aquatic Environment - Long-term Hazard Category 1
EH C2	Hazardous to the Aquatic Environment - Long-term Hazard Category 2
FL 3	Flammable Liquid, Hazard Category 3
H226	Flammable liquid and vapour.
H302	Harmful if swallowed.



Version: 24 (08/08/2023)

SAFETY DATA SHEET

In accordance with REACH Regulation EC No.1907/2006

Product: CRACKLING LOG FIRE FRAGRANCE 903787

Version: 24

H304 May be fatal if swallowed and enters airways. H315 Causes skin irritation. H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. H210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell.
H317 May cause an allergic skin reaction. H319 Causes serious eye irritation. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell.
H319 Causes serious eye irritation. H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell.
H410 Very toxic to aquatic life with long lasting effects. H411 Toxic to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell.
H411 Toxic to aquatic life with long lasting effects. P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell.
P210 Keep away from heat, sparks, open flames and hot surfaces No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell.
P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician if you feel unwell.
P241 Use explosion-proof electrical, ventilating and lighting equipment. P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P242 Use only non-sparking tools. P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P243 Take precautionary measures against static discharge. P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P261 Avoid breathing vapour or dust. P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P264 Wash hands and other contacted skin thoroughly after handling. P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P270 Do not eat, drink or smoke when using this product. P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P272 Contaminated work clothing should not be allowed out of the workplace. P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P273 Avoid release to the environment. P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P280 Wear protective gloves/eye protection/face protection. P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P301/310 IF SWALLOWED: Immediately call a POISON CENTER or doctor/physician. P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P301/312 IF SWALLOWED: call a POISON CENTER or doctor/physician if you feel unwell.
P302/352 IF ON SKIN: Wash with plenty of soap and water.
P303/361/353 IF ON SKIN (or hair): Remove/take off immediately all contaminated clothing. Rinse skin with water/show
P305/351/338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy do. Continue rinsing.
P330 Rinse mouth.
P331 Do not induce vomiting.
P332/313 If skin irritation occurs: Get medical advice/attention.
P333/313 If skin irritation or rash occurs: Get medical advice/attention.
P337/313 If eye irritation persists: Get medical advice/attention.
P362 Take off contaminated clothing and wash before reuse.
P363 Wash contaminated clothing before reuse.
P370/378 In case of fire: Use carbon dioxide, dry chemical, foam for extinction.
P391 Collect spillage.
P403/235 Store in a well-ventilated place. Keep cool.
P405 Store locked up.
P501 Dispose of contents/container to approved disposal site, in accordance with local regulations.
SCI 2 Skin Corrosion / Irritation Category 2
SS 1B Sensitization - Skin Category 1B

The information in this safety data sheet is to the best of our knowledge true and accurate but all data, instructions, recommendations and/or suggestions are made without guarantee.