



Stain & Seal Experts™ - Fence & Deck Stains Technical Data Sheet

Stain & Seal Experts™ Fence & Deck Stains are contractor grade, solvent-free, mineral oil-based stain & sealers - the best and safest way to preserve your wood! Available in 18 transparent, semi-transparent and semi-solid color options.

Contractor Grade Stain & Sealers

Easy to apply, easy to clean-up, and no foul odors.
Extra-low VOC formula is safer for you, and the environment.

Product Description: Stain & Seal Experts™ wood stain & sealers are a proprietary blend of mineral oil, finely ground pigments and, high-quality resins that preserve, protect and, restore wood by penetrating deep and leaving no film. Stain & Seal Experts™ stains contain no linseed or other vegetable oils that promote fungus, algae or, other organic growth. Stain & Seal Experts™ stains may be used on any exterior and some interior projects, including western red cedar, pine, pressure treated, Japanese cedar, yellow cedar, cypress, douglas fir, California redwood, and spruce.

**No peeling, cracking, or chipping –
No drips, runs, or lap marks!**

Compatibility: Stain & Seal Experts™ stain colors may be mixed to achieve custom colors. *Do not mix Stain & Seal Experts™ stains with other stain types, or brands.*

Finish: Stain & Seal Experts™ dries to a matte finish. Over application can cause excessive dry times and/or premature finish failure. Always follow application instructions.

Surface Prep: Surfaces must be cleaned and free of dust, dirt, organic growth, oil, or grease. Remove all old coatings and always neutralize any oxidizing chemicals like bleach or wood strippers with Stain & Seal Experts™ Wood Brightener. Be sure your lumber has seasoned the proper amount of time, and the moisture content is below 12.9%.

Technical Specifications

VOC Content

Less than 50 g/L.
Meets Federal & 50 state VOC requirements.

Application Temperature

Can be applied in any temperature and in direct sunlight. Cold temperatures may extend dry time.

Moisture Content

Wood should be 12.9% moisture content or less.

Coverage on Fencing

Apply in a flood coat manner at 125-150 sq-ft./Gal.

Coverage on Decking

Apply & back brush at 175-200 sq-ft./Gal.

TECHNICAL DATA SHEET

Application: Always mix Stain & Seal Experts™ with a power or drill mixer, being sure to get all settled pigments up and off the bottom of the pail. **Mix for at least two minutes before using.** Pour all pails of stain together in one master container to ensure color uniformity. **Test the stain color on a small area to ensure the color is satisfactory.** Apply with a brush, roller, stain mitt, pump-up sprayer, airless sprayer, or low-pressure HVLP systems. Apply in either a heavy flood coat, or multiple light coats. Always brush away or wipe up any puddling stain, **especially on flat surfaces.** Dry time will always depend on the weather, temperature, and surface conditions. Colors will be darker when first applied and settle to the correct color after one to two weeks.



Caution: *This product is combustible. Do not store or use near a flame or heat source. Do not store or use near a flame or heat source.*

In case of fire: Use foam, dry chemical, water fog nozzle, or carbon dioxide extinguisher.

Disposal: Absorb spills or leaks into inert material and dispose of them according to your local disposal agency. **Do not apply directly over waterways, near-surface water, or below a high tide mark area. Do not apply in a way that will come in contact with humans or pets. Do not use on surfaces that come in contact with food.** Apply Stain & Seal Experts™ stains only as specified on the label. Always keep stain containers sealed when not in use.

Always wear proper PPE: Wear approved goggles, rubber gloves, protective suit, head sock and a NIOSH/MSHA approved respirator when using this product. Only use in well-ventilated areas and keep away from food, pets, and living plants and foliage.

**FENCE
ARMOR**®

Have additional questions?

1-888-289-5617 • GetIt@FenceArmor.com • FenceArmor.com

Fence Armor® is a Registered Distributor for Stain & Seal Experts™ products.

Stain & Seal Experts™ – Warranty

Stain & Seal Experts™ Fence and Deck Stains guarantee the contents of the container and warrant the finish for up to 2-3 years depending on product type and color. Clear Sealers are not warrantied. Transparent and semi-transparent fence stains and deck stains are warrantied for 2 years. Semi-solid Fence Stains are warrantied for 3 years. To maintain the warranty, stained surfaces must be gently washed annually and a maintenance stain coat applied every 2 years. Labor costs are not covered in any way by this warranty. The warranty covers only the purchase price of the material.

