



SAFETY DATA SHEET

This safety data sheet was created pursuant to the requirements of: US OSHA Hazard Communication Standard (29 CFR 1910.1200) and Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR)

Issuing Date 21-Sep-2018

Revision date 21-Sep-2018

Revision Number 1

1. Identification

Product identifier

Product Name 100P Industrial Paint Marker/100P FL/ 130P Broad Tip Industrial Paint Marker Most Colors

Other means of identification

Product Code(s) 100P: #10201 Black, #10202 Blue, #10203 Green, #10204 Red, #10205 White, #10206 Yellow, #10207 Orange, #10209 Bright Green, #10211 Pink, #10212 Violet, #10213 Light Blue
100P Fine Line: #10201FL Black, #10202FL Blue, #10203FL Green, #10204FL Red, #10205FL White, #10206FL Yellow, #10207FL Orange, #10209FL Bright Green, #10211FL Pink, #10212FL Violet, #10213FL Light Blue
130P: #13001 Black, #13002 Blue, #13003 Green, #13004 Red, #13005 White, #13006 Yellow, #13007 Orange, #13008 Light Blue, #13009 Bright Green, #13011 Pink, #13012 Violet

UN/ID no UN1210

Synonyms 100P/130P

Recommended use of the chemical and restrictions on use

Recommended use Industrial Markers

Restrictions on use Keep away from children. Not to be used for skin.

Details of the supplier of the safety data sheet

Manufacturer Address

U-Mark, Inc
102 Iowa Ave.
Belleville, IL 62220
TEL: 618-235-7500

Emergency telephone number

Emergency Telephone 24-hour Emergency Phone: Infotrac 1-800-535-5053 (USA & Canada), 1-352-323-3500 (International)

2. Hazard(s) identification

Classification

This product is an article as defined by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200) and Canada WHMIS 2015, which includes the amended Hazardous Products Act (HPA). No exposure to hazardous chemicals is expected to occur during intended product use. Misuse of the product may result in exposure to hazardous chemicals.

Appearance colored, opaque liquid

Physical state Liquid

Odor Hydrocarbon-like

Label elements

Hazard statements

This product is an article as defined by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200) and Canada WHMIS 2015, which includes the amended Hazardous Products Act (HPA). No exposure to hazardous chemicals is expected to occur during intended product use. Misuse of the product may result in exposure to hazardous chemicals.

Other information

Not applicable

3. Composition/information on ingredients

Substance

Not applicable.

Mixture

Synonyms 100P/130P.

Chemical name	CAS No.	Weight-%	Hazardous Material Information Review Act registry number (HMIRA registry #)	Date HMIRA filed and date exemption granted (if applicable)
Xylene	1330-20-7	30-60	-	-
Titanium dioxide	13463-67-7	0-30	-	-
Ethylbenzene	100-41-4	5-15	-	-
Carbon black	1333-86-4	0-10	-	-
3H-Pyrazol-3-one, 4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)] bis[2,4-dihydro-5-methyl-2-phenyl-	3520-72-7	0-5	-	-
C.I. Pigment Blue 15	147-14-8	0-5	-	-
Silicon dioxide	7631-86-9	0-2	-	-
Aluminum hydroxide	21645-51-2	0-5	-	-
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl	5468-75-7	0-0.5	-	-
Toluene	108-88-3	0.1-1	-	-

4. First-aid measures

Description of first aid measures

General advice

Under normal conditions of use first aid is not required.

Inhalation

If experiencing respiratory symptoms: Call a POISON CENTER or doctor.

Eye contact

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if symptoms occur.

Skin contact

Wash skin with soap and water. Get medical attention if irritation develops and persists.

Ingestion

IF SWALLOWED: Get medical attention if symptoms occur.

Most important symptoms and effects, both acute and delayed

Symptoms None known.

Indication of any immediate medical attention and special treatment needed

Note to physicians Treat symptomatically.

5. Fire-fighting measures

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Unsuitable extinguishing media None known.

Specific hazards arising from the chemical The ink contained in this product is flammable but not readily ignited.

Explosion data

Sensitivity to mechanical impact None.

Sensitivity to static discharge None.

Special protective equipment for fire-fighters Firefighters should wear self-contained breathing apparatus and full firefighting turnout gear. Use personal protection equipment.

6. Accidental release measures

Personal precautions, protective equipment and emergency procedures

Personal precautions Remove all sources of ignition.

Methods and material for containment and cleaning up

Methods for containment Prevent further leakage or spillage if safe to do so.

Methods for cleaning up Pick up and transfer to properly labeled containers.

7. Handling and storage

Precautions for safe handling

Advice on safe handling Handle in accordance with good industrial hygiene and safety practice. Remove all sources of ignition.

Conditions for safe storage, including any incompatibilities

Storage Conditions Keep containers tightly closed in a cool, well-ventilated place.

8. Exposure controls/personal protection

Control parameters

Exposure Limits

Chemical name	ACGIH TLV	OSHA PEL	NIOSH IDLH	
Xylene 1330-20-7	STEL: 150 ppm TWA: 100 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 655 mg/m ³	-	
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 15 mg/m ³ total dust (vacated) TWA: 10 mg/m ³ total dust	IDLH: 5000 mg/m ³	
Ethylbenzene 100-41-4	TWA: 20 ppm	TWA: 100 ppm TWA: 435 mg/m ³ (vacated) TWA: 100 ppm (vacated) TWA: 435 mg/m ³ (vacated) STEL: 125 ppm (vacated) STEL: 545 mg/m ³	IDLH: 800 ppm TWA: 100 ppm TWA: 435 mg/m ³ STEL: 125 ppm STEL: 545 mg/m ³	
Carbon black 1333-86-4	TWA: 3 mg/m ³ inhalable particulate matter	TWA: 3.5 mg/m ³ (vacated) TWA: 3.5 mg/m ³	IDLH: 1750 mg/m ³ TWA: 3.5 mg/m ³ TWA: 0.1 mg/m ³ Carbon black in presence of Polycyclic aromatic hydrocarbons PAH	
C.I. Pigment Blue 15 147-14-8	TWA: 1 mg/m ³ Cu dust and mist	-	IDLH: 100 mg/m ³ Cu dust and mist TWA: 1 mg/m ³ Cu dust and mist	
Silicon dioxide 7631-86-9	No data available	TWA: 50 µg/m ³ excludes construction work, agricultural operations, and exposures that result from the processing of sorptive clays (vacated) TWA: 6 mg/m ³ <1% Crystalline silica TWA: 20 mppcf : (80)/(%) SiO ₂ mg/m ³ TWA	IDLH: 3000 mg/m ³ TWA: 6 mg/m ³	
Aluminum hydroxide 21645-51-2	TWA: 1 mg/m ³ respirable particulate matter	-	-	
Toluene 108-88-3	TWA: 20 ppm	TWA: 200 ppm (vacated) TWA: 100 ppm (vacated) TWA: 375 mg/m ³ (vacated) STEL: 150 ppm (vacated) STEL: 560 mg/m ³ Ceiling: 300 ppm	IDLH: 500 ppm TWA: 100 ppm TWA: 375 mg/m ³ STEL: 150 ppm STEL: 560 mg/m ³	
Chemical name	Alberta	British Columbia	Ontario	Quebec
Xylene 1330-20-7	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm STEL: 150 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 150 ppm STEL: 651 mg/m ³
Titanium dioxide 13463-67-7	TWA: 10 mg/m ³	TWA: 10 mg/m ³ TWA: 3 mg/m ³	TWA: 10 mg/m ³	TWA: 10 mg/m ³
Ethylbenzene 100-41-4	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm	TWA: 20 ppm	TWA: 20 ppm	TWA: 100 ppm TWA: 434 mg/m ³ STEL: 125 ppm

	STEL: 543 mg/m ³			STEL: 543 mg/m ³
Carbon black 1333-86-4	TWA: 3.5 mg/m ³	TWA: 3 mg/m ³	TWA: 3 mg/m ³	TWA: 3.5 mg/m ³
Aluminum hydroxide 21645-51-2		TWA: 1.0 mg/m ³	TWA: 1 mg/m ³	
Toluene 108-88-3	TWA: 50 ppm TWA: 188 mg/m ³ Skin	TWA: 20 ppm Adverse reproductive effect	TWA: 20 ppm	TWA: 50 ppm TWA: 188 mg/m ³ Skin

Appropriate engineering controls

Engineering controls Showers
 Eyewash stations
 Ventilation systems.

Individual protection measures, such as personal protective equipment

Eye/face protection No special protective equipment required.

Skin and body protection No special protective equipment required.

Respiratory protection No protective equipment is needed under normal use conditions. If exposure limits are exceeded or irritation is experienced, ventilation and evacuation may be required.

General hygiene considerations Handle in accordance with good industrial hygiene and safety practice.

9. Physical and chemical properties

Information on basic physical and chemical properties

Physical state Liquid
Appearance colored, opaque liquid
Color Varies
Odor Hydrocarbon-like
Odor threshold No information available

<u>Property</u>	<u>Values</u>	<u>Remarks • Method</u>
pH	No data available	None known
Melting point / freezing point	No data available	None known
Boiling point / boiling range	119 - 207 °C / 246.2 - 404.6 °F	(Liquid Ink only)
Flash point	24 - 29 °C / 75.2 - 84.2 °F	(Liquid Ink only)
Evaporation rate	No data available	None known
Flammability (solid, gas)	No data available	None known
Flammability Limit in Air		None known
Upper flammability or explosive limits	7%	
Lower flammability or explosive limits	1%	
Vapor pressure	0.67 - 0.93 kPa (5 - 7 mmHg)	None known
Vapor density	> 1	(air = 1)
Relative density	0.9	None known
Water solubility	Insoluble in water	None known
Solubility(ies)	No data available	None known
Partition coefficient	No data available	None known
Autoignition temperature	No data available	None known
Decomposition temperature	No data available	None known
Kinematic viscosity	No data available	None known

Dynamic viscosity No data available None known

Other information

Explosive properties No information available.
Oxidizing properties No information available.
Softening point No information available
Molecular weight No information available
VOC Content (%) 40-65
Liquid Density No information available
Bulk density No information available

10. Stability and reactivity

Reactivity No information available.
Chemical stability Stable under normal conditions.
Possibility of hazardous reactions None under normal processing.
Conditions to avoid Heat, flames and sparks.
Incompatible materials None known based on information supplied.
Hazardous decomposition products None known based on information supplied.

11. Toxicological information

Information on likely routes of exposure

Inhalation Specific test data for the substance or mixture is not available.
Eye contact Specific test data for the substance or mixture is not available.
Skin contact Specific test data for the substance or mixture is not available.
Ingestion Specific test data for the substance or mixture is not available.

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms None known.

Acute toxicity

Numerical measures of toxicity

No information available

Component Information

Chemical name	Oral LD50	Dermal LD50	Inhalation LC50
Xylene 1330-20-7	= 3500 mg/kg (Rat)	> 4350 mg/kg (Rabbit) > 1700 mg/kg (Rabbit)	= 29.08 mg/L (Rat) 4 h = 5000 ppm (Rat) 4 h
Titanium dioxide 13463-67-7	> 10000 mg/kg (Rat)	-	-
Ethylbenzene 100-41-4	= 3500 mg/kg (Rat)	= 15400 mg/kg (Rabbit)	= 17.4 mg/L (Rat) 4 h
Carbon black 1333-86-4	> 15400 mg/kg (Rat)	> 3 g/kg (Rabbit)	-
3H-Pyrazol-3-one,	> 5 g/kg (Rat)	-	-

4,4'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2,4-dihydro-5-methyl-2-phenyl-3520-72-7			
C.I. Pigment Blue 15 147-14-8	> 10000 mg/kg (Rat)	-	-
Silicon dioxide 7631-86-9	= 7900 mg/kg (Rat)	> 2000 mg/kg (Rabbit)	> 2.2 mg/L (Rat) 1 h
Aluminum hydroxide 21645-51-2	> 5000 mg/kg (Rat)	-	-
Butanamide, 2,2'-[(3,3'-dichloro[1,1'-biphenyl]-4,4'-diyl)bis(azo)]bis[2,4-dihydro-5-methyl-2-phenyl-5468-75-7	> 5 g/kg (Rat)	-	-
Toluene 108-88-3	= 2600 mg/kg (Rat)	= 12000 mg/kg (Rabbit)	= 12.5 mg/L (Rat) 4 h

Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation No information available.

Serious eye damage/eye irritation No information available.

Respiratory or skin sensitization No information available.

Germ cell mutagenicity No information available.

Carcinogenicity This product contains titanium dioxide in a non-respirable form. Inhalation of titanium dioxide is unlikely to occur from exposure to this product. This product contains carbon black in a non-respirable form. Inhalation of carbon black is unlikely to occur from exposure to this product.

The table below indicates whether each agency has listed any ingredient as a carcinogen.

Chemical name	ACGIH	IARC	NTP	OSHA
Xylene 1330-20-7	-	Group 3	-	-
Titanium dioxide 13463-67-7	-	Group 2B	-	X
Ethylbenzene 100-41-4	A3	Group 2B	-	X
Carbon black 1333-86-4	A3	Group 2B	-	X
Silicon dioxide 7631-86-9	-	Group 3	Known	X
Toluene 108-88-3	-	Group 3	-	-

Legend

ACGIH (American Conference of Governmental Industrial Hygienists)

A3 - Animal Carcinogen

IARC (International Agency for Research on Cancer)

Group 2B - Possibly Carcinogenic to Humans

NTP (National Toxicology Program)

Known - Known Carcinogen

OSHA (Occupational Safety and Health Administration of the US Department of Labor)

X - Present

Reproductive toxicity No information available.

STOT - single exposure No information available.

STOT - repeated exposure No information available.

Aspiration hazard No information available.

12. Ecological information

Ecotoxicity The environmental impact of this product has not been fully investigated.

Chemical name	Algae/aquatic plants	Fish	Toxicity to microorganisms	Crustacea
Xylene 1330-20-7	-	LC50: =13.4mg/L (96h, Pimephales promelas) LC50: 2.661 - 4.093mg/L (96h, Oncorhynchus mykiss) LC50: 13.5 - 17.3mg/L (96h, Oncorhynchus mykiss) LC50: 13.1 - 16.5mg/L (96h, Lepomis macrochirus) LC50: =19mg/L (96h, Lepomis macrochirus) LC50: 7.711 - 9.591mg/L (96h, Lepomis macrochirus) LC50: 23.53 - 29.97mg/L (96h, Pimephales promelas) LC50: =780mg/L (96h, Cyprinus carpio) LC50: >780mg/L (96h, Cyprinus carpio) LC50: 30.26 - 40.75mg/L (96h, Poecilia reticulata)	-	EC50: =3.82mg/L (48h, water flea) LC50: =0.6mg/L (48h, Gammarus lacustris)
Ethylbenzene 100-41-4	EC50: 1.7 - 7.6mg/L (96h, Pseudokirchneriella subcapitata) EC50: 2.6 - 11.3mg/L (72h, Pseudokirchneriella subcapitata) EC50: =4.6mg/L (72h, Pseudokirchneriella subcapitata) EC50: >438mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 18.0mg/L (96h, Oncorhynchus mykiss) LC50: 7.55 - 11mg/L (96h, Pimephales promelas) LC50: 9.1 - 15.6mg/L (96h, Pimephales promelas) LC50: =32mg/L (96h, Lepomis macrochirus) LC50: =4.2mg/L (96h, Oncorhynchus mykiss) LC50: =9.6mg/L (96h, Poecilia reticulata)	-	EC50: 1.8 - 2.4mg/L (48h, Daphnia magna)
Carbon black 1333-86-4	-	-	-	EC50: >5600mg/L (24h, Daphnia magna)
C.I. Pigment Blue 15 147-14-8	-	LC50: >100mg/L (48h, Oryzias latipes)	-	-
Silicon dioxide 7631-86-9	EC50: =440mg/L (72h, Pseudokirchneriella subcapitata)	LC50: =5000mg/L (96h, Brachydanio rerio)	-	EC50: =7600mg/L (48h, Ceriodaphnia dubia)
Toluene 108-88-3	EC50: =12.5mg/L (72h, Pseudokirchneriella subcapitata) EC50: >433mg/L (96h, Pseudokirchneriella subcapitata)	LC50: 11.0 - 15.0mg/L (96h, Lepomis macrochirus) LC50: 14.1 - 17.16mg/L (96h, Oncorhynchus mykiss) LC50: 15.22 - 19.05mg/L (96h, Pimephales promelas) LC50: 5.89 - 7.81mg/L (96h, Oncorhynchus mykiss)	-	EC50: 5.46 - 9.83mg/L (48h, Daphnia magna) EC50: =11.5mg/L (48h, Daphnia magna)

		LC50: 50.87 - 70.34mg/L (96h, Poecilia reticulata) LC50: =12.6mg/L (96h, Pimephales promelas) LC50: =28.2mg/L (96h, Poecilia reticulata) LC50: =5.8mg/L (96h, Oncorhynchus mykiss) LC50: =54mg/L (96h, Oryzias latipes)		
--	--	--	--	--

Persistence and degradability No information available.

Bioaccumulation There is no data for this product.

Component Information

Chemical name	Partition coefficient
Xylene 1330-20-7	2.77 - 3.15
Ethylbenzene 100-41-4	3.2
C.I. Pigment Blue 15 147-14-8	6.6
Toluene 108-88-3	2.7

Other adverse effects No information available.

13. Disposal considerations

Waste treatment methods

Waste from residues/unused products Dispose of in accordance with local regulations. Dispose of waste in accordance with environmental legislation.

Contaminated packaging Do not reuse empty containers.

Chemical name	RCRA	RCRA - Basis for Listing	RCRA - D Series Wastes	RCRA - U Series Wastes
Xylene 1330-20-7	-	Included in waste stream: F039	-	U239
Ethylbenzene 100-41-4	-	Included in waste stream: F039	-	-
Toluene 108-88-3	U220	Included in waste streams: F005, F024, F025, F039, K015, K036, K037, K149, K151	-	U220

Chemical name	RCRA - Halogenated Organic Compounds	RCRA - P Series Wastes	RCRA - F Series Wastes	RCRA - K Series Wastes
Toluene 108-88-3	-	-	Toxic waste waste number F025 Waste description: Condensed light ends, spent filters and filter aids, and spent desiccant wastes from the production of certain chlorinated aliphatic	-

			hydrocarbons, by free radical catalyzed processes. These chlorinated aliphatic hydrocarbons are those having carbon chain lengths ranging from one to and including five, with varying amounts and positions of chlorine substitution.	
--	--	--	--	--

Chemical name	California Hazardous Waste Status
Xylene 1330-20-7	Toxic Ignitable
Ethylbenzene 100-41-4	Toxic Ignitable
C.I. Pigment Blue 15 147-14-8	Toxic
Toluene 108-88-3	Toxic Ignitable

14. Transport information

DOT

UN/ID no UN1210
 Proper shipping name PRINTING INK
 Hazard class 3
 Packing group III
 Special Provisions B1, IB3, T2, TP1, 367
 Description UN1210, PRINTING INK, 3, III, Limited Quantity
 Emergency Response Guide Number 129

TDG

UN/ID no UN1210
 Proper shipping name PRINTING INK
 Hazard class 3
 Packing group III
 Description UN1210, PRINTING INK, 3, III, Limited Quantity

ICAO (air)

UN/ID no UN1210
 Proper shipping name PRINTING INK
 Hazard class 3
 Packing group III
 Special Provisions A3, A72, A192
 Description UN1210, PRINTING INK, 3, III

IATA

UN number UN1210
 UN proper shipping name Printing ink
 Transport hazard class(es) 3
 Packing group III
 ERG Code 3L
 Description UN1210, Printing ink, 3, III

IMDG

UN number UN1210

UN proper shipping name PRINTING INK
Transport hazard class(es) 3
Packing group III
EmS-No F-E, S-D
Special Provisions 163, 223, 367, 955
Description UN1210, PRINTING INK, 3, III, (24°C C.C.), Limited Quantity

RID

UN number UN1210
UN proper shipping name PRINTING INK
Transport hazard class(es) 3
Packing group III
Classification code F1
Description UN1210, PRINTING INK, 3, III, Limited Quantity
Labels 3

ADR

UN number UN1210
UN proper shipping name PRINTING INK
Transport hazard class(es) 3
Packing group III
Classification code F1
Tunnel restriction code (D/E)
Special Provisions 163, 367
Description UN1210, PRINTING INK, 3, III, Limited Quantity
Labels 3

ADN

UN proper shipping name PRINTING INK
Transport hazard class(es) 3
Packing group III
Classification code F1
Special Provisions 163, 640E
Description UN1210, PRINTING INK, 3, III, Limited Quantity
Hazard label(s) 3
Limited quantity (LQ) 5 L
Ventilation VE01

15. Regulatory information

Safety, health and environmental regulations/legislation specific for the substance or mixture

International Regulations

The Montreal Protocol on Substances that Deplete the Ozone Layer Not applicable

The Stockholm Convention on Persistent Organic Pollutants Not applicable

The Rotterdam Convention Not applicable

International Inventories

TSCA Contact supplier for inventory compliance status.
DSL/NDL Contact supplier for inventory compliance status.
EINECS/ELINCS Contact supplier for inventory compliance status.
ENCS Contact supplier for inventory compliance status.
IECSC Contact supplier for inventory compliance status.
KECL Contact supplier for inventory compliance status.
PICCS Contact supplier for inventory compliance status.
AICS Contact supplier for inventory compliance status.

Legend:

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory

DSL/NDL - Canadian Domestic Substances List/Non-Domestic Substances List
EINECS/ELINCS - European Inventory of Existing Chemical Substances/European List of Notified Chemical Substances
ENCS - Japan Existing and New Chemical Substances
IECSC - China Inventory of Existing Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
AICS - Australian Inventory of Chemical Substances

US Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42).

Chemical name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
Xylene 1330-20-7	100 lb	-	-	X
Ethylbenzene 100-41-4	1000 lb	X	X	X
C.I. Pigment Blue 15 147-14-8	-	X	-	-
Toluene 108-88-3	1000 lb	X	X	X

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302).

Chemical name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	Reportable Quantity (RQ)
Xylene 1330-20-7	100 lb	-	RQ 100 lb final RQ RQ 45.4 kg final RQ
Ethylbenzene 100-41-4	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ
Toluene 108-88-3	1000 lb	-	RQ 1000 lb final RQ RQ 454 kg final RQ

US State Regulations

California Proposition 65

The classification listed below only applies to respirable Titanium dioxide, respirable Carbon black, and respirable Silicon dioxide. This product contains the following Proposition 65 chemicals:

Chemical name	California Proposition 65
Titanium dioxide - 13463-67-7	Carcinogen
Ethylbenzene - 100-41-4	Carcinogen
Carbon black - 1333-86-4	Carcinogen
Silicon dioxide - 7631-86-9	Carcinogen
Toluene - 108-88-3	Developmental

U.S. State Right-to-Know Regulations

US State Regulations

Chemical name	New Jersey	Massachusetts	Pennsylvania
Xylene 1330-20-7	X	X	X
Titanium dioxide 13463-67-7	X	X	X
Ethylbenzene 100-41-4	X	X	X
Carbon black 1333-86-4	X	X	X
C.I. Pigment Blue 15 147-14-8	X	-	X
Toluene 108-88-3	X	X	X

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. Other information

NFPA	Health hazards 0	Flammability 3	Instability 0	Physical and chemical properties -
HMIS	Health hazards 0	Flammability 3	Physical hazards 0	Personal protection X

Key or legend to abbreviations and acronyms used in the safety data sheet

Legend Section 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

TWA	TWA (time-weighted average)	STEL	STEL (Short Term Exposure Limit)
Ceiling	Maximum limit value	*	Skin designation

Key literature references and sources for data used to compile the SDS

- Agency for Toxic Substances and Disease Registry (ATSDR)
- U.S. Environmental Protection Agency ChemView Database
- European Food Safety Authority (EFSA)
- EPA (Environmental Protection Agency)
- Acute Exposure Guideline Level(s) (AELG(s))
- U.S. Environmental Protection Agency Federal Insecticide, Fungicide, and Rodenticide Act
- U.S. Environmental Protection Agency High Production Volume Chemicals
- Food Research Journal
- Hazardous Substance Database
- International Uniform Chemical Information Database (IUCLID)
- Japan GHS Classification
- Australia National Industrial Chemicals Notification and Assessment Scheme (NICNAS)
- NIOSH (National Institute for Occupational Safety and Health)
- National Library of Medicine's ChemID Plus (NLM CIP)
- National Library of Medicine's PubMed database (NLM PUBMED)
- National Toxicology Program (NTP)
- New Zealand's Chemical Classification and Information Database (CCID)
- Organization for Economic Co-operation and Development Environment, Health, and Safety Publications
- Organization for Economic Co-operation and Development High Production Volume Chemicals Program
- Organization for Economic Co-operation and Development Screening Information Data Set
- RTECS (Registry of Toxic Effects of Chemical Substances)
- World Health Organization

Issuing Date 21-Sep-2018

Revision date 21-Sep-2018

Revision Note Initial Release.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

End of Safety Data Sheet