

SAFETY DATA SHEET

Revision Date 26-Jul-2018 **Revision Number 1** Issuing Date 25-Jul-2018

This document complies with the US OSHA Hazard Communication Standard (29 CFR 1910.1200), Canada WHMIS 2015 which includes the amended Hazardous Products Act (HPA) and the Hazardous Products Regulation (HPR), and Mexico's NMX-R-019-SC-2011.

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND THE COMPANY/UNDERTAKING

GHS product identifier

100P Industrial Paint Marker/100P FL/ 130P Broad Tip Industrial Paint Marker -**Product Name**

Silver and Gold

Other means of identification

100P #10210 Silver, #10214 Gold, 100P FL #10210FL Silver, #10214FL Gold, 130P

Product Code(s) #13010 Silver, #13014 Gold

UN-Number UN1210

Synonyms None

Recommended use of the chemical and restrictions on use

Recommended Use Solvent based marker

Keep away from children. Not for use on skin. Uses advised against

Supplier's details

Supplier Address

U-Mark, Inc 102 Iowa Ave. Belleville, IL 62220 TEL: 618-235-7500

Emergency telephone number

Emergency Telephone 24-hour Emergency Phone: Infotrac 1-800-535-5053 (USA & Canada), 1-352-323-3500 Number

(International)

2. HAZARDS IDENTIFICATION

Classification

This product is an article as defined by the OSHA Hazard Communication Standard 2012 (29 CFR 1910.1200), Canada WHMIS 2015, which includes the amended Hazardous Products Act (HPA) and the Hazardous Product Regulations (HPR), and Mexico's NMX-R-019-SC-2011. No exposure to hazardous chemicals is expected to occur during intended product use. Misuse of the product may result in exposure to hazardous chemicals.

Label Elements

Signal Word

None

Physical and Health Hazards Not Otherwise Classified

Not applicable.

Precautionary Statements

Prevention

None

General Advice

None

Storage

None

Disposal

None

Other information

No information available

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No		Hazardous Material Information Review Act registry number (HMIRA registry #)	
n-Butyl acetate	123-86-4	40-50	-	-
Ethyl acetate	141-78-6	35-45	-	-
Propylene glycol monomethyl ether acetate	108-65-6	0-5	-	-

4. FIRST AID MEASURES

Description of necessary first-aid measures

General Advice Under normal conditions of use first aid is not required.

Eye Contact IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. Call a physician or Poison Control Center

immediately.

Skin Contact Wash skin with soap and water. Get medical attention if irritation develops and persists.

Inhalation If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.

Ingestion IF SWALLOWED: Call a POISON CENTER or doctor/ physician if you feel unwell.

Most important symptoms/effects, acute and delayed

Most Important Symptoms/Effects None known

Indication of immediate medical attention and special treatment needed, if necessary

Notes to Physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media Use extinguishing measures that are appropriate to local circumstances and the

surrounding environment.

Unsuitable Extinguishing Media None

100P Industrial Paint Marker/100P FL/ 130P Broad Tip Industrial Paint Marker - Silver and Gold

Revision Date 26-Jul-2018

Specific Hazards Arising from the The ink contained in this product is flammable but not readily ignited.

Chemical

Explosion Data

Sensitivity to Mechanical Impact None.
Sensitivity to Static Discharge None.

Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH

(approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

Personal Precautions Remove all sources of ignition.

Environmental Precautions

Environmental PrecautionsAvoid release to the environment. Dispose of contents/container to an approved waste

disposal plant. See Section 12 for additional Ecological Information.

Methods and materials for containment and cleaning up

Methods for Containment None required.

Methods for Cleaning Up Pick up and transfer to properly labeled containers.

7. HANDLING AND STORAGE

Precautions for safe handling

Handling Keep away from open flames, hot surfaces and sources of ignition.

Conditions for safe storage, including any incompatibilities

Storage Store in a well-ventilated place. Keep cool.

Incompatible Products

None known based on information supplied.

8. EXPOSURE CONTROLS / PERSONAL PROTECTION

Control parameters

Exposure Guidelines The following exposure limits are provided for information only; exposure is not expected

under normal conditions of use or storage.

Chemical Name	ACGIH TLV OSHA PEL		NIOSH IDLH	
n-Butyl acetate	n-Butyl acetate STEL: 150 ppm		IDLH: 1700 ppm	
123-86-4	TWA: 50 ppm	TWA: 710 mg/m ³	TWA: 150 ppm	
		(vacated) TWA: 150 ppm	TWA: 710 mg/m ³	
		(vacated) TWA: 710 mg/m ³	STEL: 200 ppm	
		(vacated) STEL: 200 ppm	STEL: 950 mg/m ³	
		(vacated) STEL: 950 mg/m ³	_	
Ethyl acetate	TWA: 400 ppm	TWA: 400 ppm	IDLH: 2000 ppm	
141-78-6		TWA: 1400 mg/m ³	TWA: 400 ppm	
		(vacated) TWA: 400 ppm	TWA: 1400 mg/m ³	
		(vacated) TWA: 1400 mg/m ³	_	

Appropriate engineering controls

Engineering Measures None under normal use conditions.

Individual protection measures, such as personal protective equipment

Eye/Face ProtectionNo protective equipment is needed under normal use conditions.Skin and Body ProtectionNo protective equipment is needed under normal use conditions.Respiratory ProtectionNo protective equipment is needed under normal use conditions.

Hygiene Measures Handle in accordance with good industrial hygiene and safety practice.

9. PHYSICAL AND CHEMICAL PROPERTIES

None known

Information on basic physical and chemical properties

Physical StateLiquid.AppearanceVaries.

Odor Mild. Odor Threshold No information available.

<u>Property</u> <u>Values</u> <u>Remarks/ - Method</u>

No data available None known **Melting Point/Range** No data available None known 96 °C / 205 °F **Boiling Point/Boiling Range** None known 23 °C / 73 °F **Flash Point** (Liquid Ink only) **Evaporation rate** No data available None known Flammability (solid, gas) No data available None known

No data available

Flammability Limits in Air

Vapor Pressure

upper flammability limit 13.5% lower flammability limit 2.1%

Vapor Density No data available None known **Relative Density** No data available None known **Specific Gravity** 9418 None known Water Solubility No data available None known Solubility in other solvents No data available None known Partition coefficient: n-octanol/waterNo data available None known **Autoignition Temperature** No data available None known **Decomposition Temperature** No data available None known No data available None known **Viscosity**

Flammable Properties Highly flammable.
Explosive Properties No data available
Oxidizing Properties No data available

Other information

VOC Content (%) No data available

10. STABILITY AND REACTIVITY

Reactivity No data available.

<u>Chemical stability</u> Stable under recommended storage conditions.

Possibility of hazardous reactions None under normal processing.

<u>Hazardous Polymerization</u> Hazardous polymerization does not occur.

<u>Conditions to avoid</u> None known based on information supplied.

Incompatible materialsNone known based on information supplied.

Hazardous decomposition products Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

Information on likely routes of exposure

Product Information Product does not present an acute toxicity hazard based on known or supplied information.

InhalationNone under normal use conditionsEye ContactNone under normal use conditions.Skin ContactNone under normal use conditions.IngestionNone under normal use conditions.

Numerical measures of toxicity - Product

The following values are calculated based on chapter 3.1 of the GHS document: Not applicable

Component Information

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
n-Butyl acetate	= 10768 mg/kg (Rat)	> 17600 mg/kg (Rabbit)	= 390 ppm (Rat) 4 h
Ethyl acetate	= 5620 mg/kg (Rat)	> 20 mL/kg(Rabbit)> 18000 mg/kg(Rabbit)	= 4000 ppm (Rat) 4 h
Propylene glycol monomethyl ether acetate	= 8532 mg/kg (Rat)	> 5 g/kg(Rabbit)	-

Symptoms related to the physical, chemical and toxicological characteristics

Symptoms None under normal use.

Delayed and immediate effects and also chronic effects from short and long term exposure

Carcinogenicity Contains no ingredient listed as a carcinogen.

Reproductive Toxicity
STOT - single exposure
STOT - repeated exposure
Aspiration Hazard
No information available
No information available
No information available.

12. ECOLOGICAL INFORMATION

Ecotoxicity Not Applicable

Chemical Name	Toxicity to Algae	Toxicity to Fish	Toxicity to Microorganisms	Daphnia Magna (Water Flea)
n-Butyl acetate 123-86-4	EC50 72 h: = 674.7 mg/L (Desmodesmus subspicatus)	LC50 96 h: 17 - 19 mg/L flow-through (Pimephales promelas) LC50 96 h: = 100 mg/L static (Lepomis macrochirus) LC50 96 h: = 62 mg/L static (Leuciscus idus)	EC50 = 70.0 mg/L 5 min EC50 = 82.2 mg/L 15 min EC50 = 959 mg/L 18 h EC50 = 98.9 mg/L 30 min	EC50 24 h: = 72.8 mg/L (Daphnia magna)
Ethyl acetate 141-78-6	EC50 48 h: = 3300 mg/L (Desmodesmus subspicatus)	LC50 96 h: 220 - 250 mg/L flow-through (Pimephales promelas) LC50 96 h: 352 - 500 mg/L semi-static (Oncorhynchus mykiss) LC50 96 h: = 484 mg/L flow-through (Oncorhynchus mykiss)	EC50 = 1180 mg/L 5 min EC50 = 1500 mg/L 15 min EC50 = 5870 mg/L 15 min EC50 = 7400 mg/L 2 h	EC50 48 h: = 560 mg/L Static (Daphnia magna)
Propylene glycol monomethyl ether acetate 108-65-6		LC50 96 h: = 161 mg/L static (Pimephales promelas)		EC50 48 h: > 500 mg/L (Daphnia magna)

Persistence and Degradability

No information available

Bioaccumulation No information available

Chemical Name	Log Pow
n-Butyl acetate	1.81
Ethyl acetate	0.6
Propylene glycol monomethyl ether acetate	0.43

Mobility No information available

Other Adverse Effects No information available.

13. DISPOSAL CONSIDERATIONS

Waste Disposal Methods Dispose of in accordance with local regulations.

Contaminated Packaging Not Applicable

14. TRANSPORT INFORMATION

DOT

UN-Number UN1210 Proper shipping name Printing ink

Hazard Class 3
Packing Group III

Description UN1210, Printing ink, 3, III, Limited Quantity

Emergency Response Guide 129

Number

TDG

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III

Description UN1210, Printing ink, 3, III, Limited Quantity

MEX

UN-Number UN1210 Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III

Description UN1210, Printing ink, 3, III, Limited Quantity

IATA

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III
ERG Code 3L

Description UN1210, Printing ink, 3, III, Limited Quantity

IMDG/IMO

UN-Number UN1210
Proper Shipping Name Printing ink

Hazard Class 3
Packing Group III
EmS No. F-E, S-D

Description UN1210, Printing ink, 3, III, (23°C c.c.), Limited Quantity

15. REGULATORY INFORMATION

International Regulations

Ozone depleting substancesNot applicablePersistent Organic PollutantsNot applicableHazardous WasteNot applicable

 Chemical Name
 Basel Convention (Hazardous Wastes)

 Ethyl acetate
 Y42

The Rotterdam Convention (Prior

Informed Consent)

Not applicable

International Convention for the Prevention of Pollution from Ships

Not applicable

(MARPOL)

International Inventories

TSCA Contact supplier for inventory compliance status DSL/NDSL Contact supplier for inventory compliance status

Legend

TSCA - United States Toxic Substances Control Act Section 8(b) Inventory DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List

U.S. Federal Regulations

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372.

SARA 311/312 Hazard Categories

Should this product meet EPCRA 311/312 Tier reporting criteria at 40 CFR 370, refer to Section 2 of this SDS for appropriate classifications. Under the amended regulations at 40 CFR 370, EPCRA 311/312 Tier II reporting for the 2017 calendar year will need to be consistent with updated hazard classifications.

Clean Water Act

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42):

Chemical Name	CWA - Reportable Quantities	CWA - Toxic Pollutants	CWA - Priority Pollutants	CWA - Hazardous Substances
n-Butyl acetate	5000 lb			Χ

CERCLA

This material, as supplied, contains one or more substances regulated as a hazardous substance under the Comprehensive Environmental Response Compensation and Liability Act (CERCLA) (40 CFR 302):

Chemical Name	Hazardous Substances RQs	Extremely Hazardous Substances RQs	RQ
n-Butyl acetate	5000 lb		RQ 5000 lb final RQ
•			RQ 2270 kg final RQ
Ethyl acetate	5000 lb		RQ 5000 lb final RQ
•			RQ 2270 kg final RQ

U.S. State Regulations

California Proposition 65

This product does not contain any Proposition 65 chemicals.

U.S. State Right-to-Know Regulations

This product does not contain any substances regulated by state right-to-know regulations.

Chemical Name	New Jersey	Massachusetts	Pennsylvania	Illinois	Rhode Island
n-Butyl acetate	X	X	X		X
Ethyl acetate	X	X	Х		Х

U.S. EPA Label Information

EPA Pesticide Registration Number Not applicable

16. OTHER INFORMATION

NFPA Health Hazard 0 Flammability 2 Instability 0 Physical and Chemical

Hazards -

HMIS Health Hazard 0 Flammability 2 Physical Hazard 0 Personal Protection X

Prepared By Product Stewardship

23 British American Blvd. Latham, NY 12110 1-800-572-6501

Issuing Date25-Jul-2018Revision Date26-Jul-2018

Revision Note New regional format.

General Disclaimer

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet