

Product Specification Sheet

100P™ Industrial Paint Marker



SPECIFICATIONS

• Item #: 10201 Black 10209 Bright Green 10202 Blue 10210 Metallic Silver

 10203 Green
 10211 Pink


 10204 Red
 10212 Violet

 10205 White
 10213 Light Blue

 10206 Yellow
 10214 Metallic Gold

 10207 Orange
 10215 Brown

10100 HD Bullet Tip







• Style: Valve Activated

• Tip Type: Bullet

• Marking Widths: 2 mm. (0.078")

• Dimensions: 5.69" L x 0.56" Ø (144 x 14 mm.) *

• Marking Temp. Range: -50° to 150° Fahrenheit (-45° to 65° C)

• Dry Time: approx. 45 sec.

Quantity/ Weight Per Box: 12ea./ 0.75 lb./ (340 g.)
Quantity/ Weight Per Case: 144ea./ 9 lb./ (4.1 kg.)

• **Directions For Use:** Shake vigorously with cap on. Press tip until inked. Replace cap after use.

* Dimensions taken w/ marker capped.

PRODUCT FEATURES

- Two available sizes for medium and fine line marking.
- Heavy duty aluminum barrel and air-tight cap withstand industrial use.
- Liquid paint is dispensed by a patented valve to ensure smooth paint flow.
- Paint is UV and weather resistant.
- Marker fits in U-Holder™

TYPICAL USES

• Marks well on rusty and oily metals, dry or damp wood, glass, plastics, rubber tape, cardboard, waxed cartons, ceramics, tiles, concrete, and more.

SAFETY INFORMATION

- Read MSDS before using (available online at www.umarkers.com).
- Keep out of reach of children. For professional use only.

Important Information

The technical information and data provided in this PSS should be considered typical and, should not be used as a specification.

Applications may vary, therefore, testing is recommended before use. Our Technical Department will be happy to work with you and help you select the best product for your application.

Rev. 04/13/2020