

## A30 Broad Tip Paint Marker



### SPECIFICATIONS

- Item # : 10301 Black 10309 Light Green
- 10302 Blue 10310 Metallic Silver
- 10303 Green 10311 Pink
- 10304 Red 10312 Violet
- 10305 White 10313 Light Blue
- 10306 Yellow 14000 Chisel Tip
- 10307 Orange 14200 Belt Holster

- Style: Valve Activated
- Tip Type: Broad Chisel Tip
- Marking Widths: 3mm., 5mm., 7mm. (0.118", 0.196", 0.275")
- Dimensions: 5.63" L x 0.8" Ø (142 x 20 mm.) \*
- Marking Temp. Range: -50° to 150° Fahrenheit (-45° to 65° C)
- Dry Time: approx. 20 sec.
- Quantity/ Weight Per Box: 6ea./ 0.7 lb./ (310 g.)
- Quantity/ Weight Per Case: 72ea./ 8 lb./ (3.7 kg.)
- **Directions For Use:** Shake vigorously with cap on. Press tip until inked. Replace cap after use.

\* Dimensions taken w/ marker capped.

### PRODUCT FEATURES

- Larger marks provide better visibility and are easier to read.
- Broad tip can mark in three widths (7, 5 and 3mm.).
- Megaflo™ patented valve accurately dispenses paint.

### TYPICAL USES

- Wherever broad, bold markers are necessary.
- Industrial marking for quality assurance, color coding and parts identification.
- Marking of tools, inventory, and work-in-progress.
- Welding, steel fabrication, construction.

### SAFETY INFORMATION

- Read MSDS before using (available online at [www.umarkers.com](http://www.umarkers.com)).
- These markers are certified as non-toxic per ASTM D4236 to contain no ingredients in quantities expected to cause significant or chronic toxicity to consumers. The markers require no precautionary labeling in accordance with the CPSC (Consumer Product Safety Commission) Regulations as mandated by Labeling of Hazardous Materials Act (LHAMA).
- Keep out of reach of children. For professional use only.



### Important Information

The technical information and data provided in this PSS should be considered typical and, should not be used as a specification. Applications may vary, therefore, testing is recommended before use. Our Technical Department will be happy to work with you and help you select the best product for your application.