

# **Commercial Air Circulators - 115V**

# **Pedestal & Wall Mounts**

**Oscillating** 





#### 2 Year Warranty

#### **Features**

- 115V, 1/3 HP, Oscillating, 1 Phase, 3 Speed, TEAO Ball Bearing Motor
- · A safety cable kit is included in all overhead mounted air circulators to prevent the fan from falling if accidentally struck or mounting fails. Single safety cable kits consist of 12 feet of 1/16" diameter cable, 2 cable clamps and instructions.
- 15' Supply Cord and Three Prong Plug Included
- · Packaged in One UPS Shippable Carton
- Wall Models Include Safety Cable
- Guard Meets OSHA Standards
- Adjustable Pedestal (5' 8')
- · Galvanized Steel Propeller
- 32" Diameter Base
- All Stocked







Tura	Tilt (In Degrees) Oscillating					
Туре	Up	Down				
Floor	20°	20°				
Wall	0°	20°				

0° = Horizontal Plane


EDP	No	Catalog No.	Prop Dia.	Fan Style	НР		CFM			RPM		F.L. Amps	Ship Wt.
EDF	NO.	Catalog No.	гтор ыа.	rail Style   Fir	High	Med	Low	High	h Med Low	r.L. Allips	Silip Wt.		
715	80	CA24OAP	24"	Adjustable Floor (S.B.)	1/4	4400	3460	2460	1100	800	600	2.8	78
715	83	CA24OW	24"	Wall Mount	1/4	4400	3460	2460	1100	000	600	2.0	46
715	81	CA30OAP	30"	Adjustable Floor (S.B.)	1/4	6100	4400	2700	1100	800	600	2.8	95
715	82	CA30OW	30"	Wall Mount	1/4	0100	4400	2700	1100	800	000	2.0	57



# **Commercial Air Circulators**

### **Component Parts / Accessories**

#### **Motors**



EDP No.	Catalog No.	Ship Wt.	Description
78018	C-1A	19	Commercial Non-Oscillating motor, 1/4 HP, 3.5 Amp, 1 Phase, 3 Speed, TEAO, ball bearing 5/8" diameter shaft, 15' power cord.
37430	0-3B	23	Commercial Oscillating motor, 1/4 HP, 1 Phase, 3 Speed, 115V, 2.8 Amps, TEAO ball bearing, 5/8" diameter shaft. <b>NOTE:</b> Oscillating motor <b>not</b> to be used in <b>UPSIDE-DOWN</b> position.

# **Capacitors**

EDP No.	Catalog No.	Ship Wt.	Description
01683	Capacitor	1	Capacitor - 8 MFD (for 78018 motors)
01430	Capacitor	1	Capacitor - 20 MFD (for 37430 motors)

#### **Pedestals**



EDP No.	Catalog No.	Ship Wt.	Description
73103	C-2030NP	7	5' high floor model. Top section provides 33 $1\!\!/\!\!2$ " counter model. Use only with I-2030B Base. (1)
73101	I-2030AP	12	5' to 8' adjustable floor model. (2)

#### **Bases**







EDP No.	Catalog No.	Ship Wt.	Description
21153	I-2030B	24	Open base. (1)
21165	A-786B-1	17	Solid base, 26" diameter. (2)
21166	A786B-2	34	Solid base, 32" diameter. (2)

#### **Wall / Vertical Mount Bracket**



EDP No.	Catalog No.	Ship Wt.	Description
75002	C-2030W	5	Use with non-oscillating commercial air circulators. Safety Cable Kit Included. NOT FOR USE WITH OSCILLATING MOTORS.

#### **Wall Mount Bracket**



EDP No.	Catalog No.	Ship Wt.	Description
37772	IAC-WB	7	Recommended for use with oscillating and non-oscillating motors. Includes Safety Cable Kit.

# **Vertical Mount Bracket**



EDP No.	Catalog No.	Ship Wt.	Description
11456	DJ-CM	7	Vertical mount for use with industrial 20",24",and 30" non-oscillating fans. Safety Cable Kit Included NOT FOR USE WITH OSCILLATING MOTORS



# **Commercial Air Circulators**

## **Component Parts / Accessories**

# **Suspension Mount Bracket**



EDP No.	Catalog No.	Ship Wt.	Description
75003	C-2030S	3	Use with commercial & industrial non-oscillating air circulators. Includes Safety Cable Kit.

## **I-Beam Mount Bracket**



EDP N	o. Catalog No.	Ship Wt.	Description
37784	IAC-BM-1	13	For use with I-Beam mounting. Includes Safety Cable Kit.  NOT FOR USE WITH OSCILLATING MOTORS

# **Safety Cable**



EDP No.	Catalog No.	Ship Wt.	Description
21204	Safety Kit	3	12' of 1/16" diameter cable, two (2) cable clamps and instructions.

## **Accessories**



EDP No.	Catalog No.	Ship Wt.	Description
70601	AMFW30K	5	Snap-on wheel kit with set screw lock for 18" to 30" pedestal fans, except I-2030B.
01723	Switch	2	2 Speed / 3 Speed Pull Chain Switch

## **Guards**



EDP No.	Catalog No.	Ship Wt.	Description
21070	AC24-G	14	24" guard.
21080	AC30-G	20	30" guard.

# **Propellers**



EDP No.	Catalog No.	Ship Wt.	Description
72458	C-24B2	5	24" Propeller with 5/8" bore, includes bushing to adapt propeller to fit motors with 1/2" shaft
73058	C-30B	7	30" Propeller with 5/8" bore, includes bushing to adapt propeller to fit motors 1ith 1/2" shaft