

36 Draffin Road Hilton, New York 14468 Phone: 585-392-3434 Toll Free: 1-800-828-6351 Sales: sales@monroefluid.com Technical: technical@monroefluid.com

Astro-Cut BCL

OVERVIEW

ASTRO-CUT BCL is a heavy duty BIOSTABLE semi-synthetic general purpose metalworking coolant containing approximately 20% mineral oil. This product, when diluted with water, forms a translucent amber emulsion which offers excellent workpiece visibility, good lubricity, and superior cooling. ASTRO-CUT BCL is designed for the machining and grinding of virtually all metals, except magnesium, and contains chlorine as an extremepressure additive for greater lubricity.

APPLICATIONS

ASTRO-CUT BCL is designed for use in metal removal operations such as all CNC milling, turning, drilling, tapping, and grinding. ASTRO-CUT BCL is also excellent on conventional machining processes and sawing applications.

ENTRATION						
	Concentration		Ratio		Refractometer	
ng	10%		1:10		5.2	
	5%		1:	20	2	2.1
	4%		1:	25	2	2.6
4%	5%	6%	7%	8%	9%	10%
1:25	1:20	1:17	1:14	1:12	1:11	1:10
2.1	2.6	3.1	3.6	4.2	4.7	5.2
	4% 1:25	Concentration 10% 5% 4% 5% 1:25 1:20	Concentration 10% 5% 4% 5% 6% 1:25 1:20 1:17	Concentration Ra 10% 1: 5% 1: 4% 5% 6% 7% 1:25 1:20 1:17 1:14	Concentration Ratio 10% 1:10 5% 1:20 4% 1:25 4% 5% 6% 7% 8% 1:25 1:20 1:17 1:14 1:12	Concentration Ratio Refract ng 10% 1:10 5 5% 1:20 2 4% 1:25 2 4% 5% 6% 7% 8% 9% 1:25 1:20 1:17 1:14 1:12 1:11

Appearance-Concentrate	Amber Liquid
Appearance - Dilution	Translucent amber
Residual Film	Soft, fluid
pH @ 20:1	9.1 ± 0.2
Specific Gravity @ 60°F	1.0 ± 0.03
Lbs/Gallon	8.34 ± 0.1
Total Chlorine, wt %	1.0
Flash point, PMCC	None