



36 Draffin Road Hilton, New York 14468
Phone: 585-392-3434
Toll Free: 1-800-828-6351
Sales: sales@monroefluid.com
Technical: technical@monroefluid.com

Cool Tool II Aerosol

OVERVIEW

COOL TOOL II Aerosol is a universal cutting and tapping fluid that performs extremely well on ALL metals including Aluminum, Stainless Steel, exotic alloys and some plastics. COOL TOOL II does NOT contain 1,1,1- trichloroethane. COOL TOOL II contains NO ozone depleting chemicals (ODCs).

APPLICATIONS

Apply COOL TOOL II Aerosol cutting and tapping fluid directly to the cutting tool using a brush, oil can or other convenient applicator. May be used for drilling, tapping, reaming, milling, turning, boring, broaching, hobbing and blanking of all metals.

MIXING

No mixing is required.

TYPICAL PROPERTIES

Appearance	Clear Amber liquid
Residual Film	Soft, oily
pH @ 20:1	N/A
Specific Gravity @ 60°F	0.91 ± 0.01
Lbs/Gallon	7.6 ± 0.1
Flash point, PMCC	182° (360°F)

Material Safety Data Sheets are available for all products.
All reasonable care has been taken to ensure
that the above information is accurate as of the date of printing.