

36 Draffin Road Hilton, New York 14468 Phone: 585-392-3434 Toll Free: 1-800-828-6351 Sales: sales@monroefluid.com Technical: technical@monroefluid.com

Monroe Cut 100 CF

OVERVIEW

MONROE CUT 100 CF is a cutting oil designed for use in screw machine applications or other machining applications that require the use of neat cutting oils. Monroe Cut 100 CF is chlorine and sulfur free allowing it to be used on a variety of metals including steel, aluminum and brass. MONROE CUT 100 CF is formulated using additives to provide a clean and efficient operating environment, compared to traditional sulfurized cutting oils.

FEATURES & BENEFITS

- · Low Odor
- · Outstanding Lubricity for Superior Finishes
- · Low Smoke
- · Operator Friendly and Clean Running
- · Compatible with all Materials
- · Exceptional Cleanliness for Visibility
- · Recommended for Screw Machines

APPLICATIONS

MONROE CUT 100 CF can be used for centerless grinding, form grinding, creep feed grinding, plunge grinding, belt grinding and flute grinding. MONROE CUT 100 CF can also be used for light machining operations.

RECOMMENDED CONCENTRATION

Use MONROE CUT 100 CF as received. Do Not mix MONROE CUT 100 CF with water.

TYPICAL PROPERTIES

| Appearance | | CI | ear Amber liquid |
|-------------------|--|----|------------------|
| Odor | | | Bland |
| Chlorine | | | Nil |
| Sulfur | | | Nil |
| Viscosity @ 100°F | | | 100 SUS |