

PREMIER FINISHES INC.

Product Safety Data Sheet 10-467 *EnviroTech Deep Base Satin

Trade Secret. See OSHA 1910.1200(i)

SECTION 1: Identification

Product identifier

Product name EnviroTech Deep Base Satin

Product number 10-467
Brand EnviroTech

Supplier's details

Name Premier Finishes Inc.

Address PO Box 3146

Oregon City, OR 97045

USA

Telephone 503-241-2770 Fax 503-241-2363

email office@premierfinishes.net

SECTION 2: Hazard identification

Classification of the substance or mixture

GHS classification in accordance with: (US) OSHA (29 CFR 1910.1200)

GHS label elements, including precautionary statements

Pictogram



Signal word Warning

Hazard statement(s)

H317 May cause an allergic skin reaction H303 May be harmful if swallowed H333 May be harmful if inhaled

Precautionary statement(s)

P280 Wear protective gloves/protective clothing/eye protection/face protection.
P501 Dispose of contents/container to an approved waste disposal plant.

P102 Keep out of reach of children.

P103 Read label before use.

SECTION 3: Composition/information on ingredients

Mixtures

Any concentration shown as a range is to protect confidentiality or due to batch variation. See also OSHA 1910.1200(i)

Hazardous components

1. Silica

Concentration 1 - 5 %

- Eye damage/irritation (chapter 3.3), Cat. 2A

H319 Causes serious eye irritation
H335 May cause respiratory irritation

2. TiO2 90

Concentration 5 - 10 % CAS no. 13463-67-7

3. Dipropylene glycol monomethyl ether

Concentration 2 - 5 % CAS no. 34590-94-8

- Flammable liquids (chapter 2.6), Cat. 4

- Specific target organ toxicity, single exposure (chapter 3.8), Cat. 3

H227 Combustible liquid

H335 May cause respiratory irritation
H336 May cause drowsiness or dizziness

4. 2,2,4-trimethyl-1, 3-pentanedol monoisobutyrate

Concentration 1 - 5 %

Trade secret statement (OSHA 1910.1200(i))

Any concentration shown as a range is to protect confidentiality or due to batch variation. See also OSHA 1910.1200(i)

SECTION 4: First-aid measures

Description of necessary first-aid measures

General advice Consult a physician. Show this safety data sheet to the doctor in attendance.

Move out of dangerous area.

If inhaled Call a poison center or doctor if you feel unwell. May cause respiratory

irritation. Signs/symptoms may include cough, sneezing, nasal discharge, headache, hoarseness, and nose and throat pain, nausea, dizziness, breathing difficulty, headaches, and loss of coordination. Effects from vapors or spray mists in poorly ventilated areas may include irritation of the

mucus membranes.

In case of skin contact Wash with plenty of soap and water for at least 15 minutes. Call a poison

center or doctor if you feel unwell. May cause skin irritation or sensitivity.

Signs/symptoms may include localized redness, cracks, swelling, itching, and

dermatitis.

In case of eye contact Rinse cautiously with water for at least 15 minutes. Remove contact lenses, if

present and easy to do. Continue rinsing. If eye irritation persists: Get medical advice/attention. May cause eye irritation. Signs/symptoms may

include redness, swelling, pain, tearing, and blurred or hazy vision.

If swallowed Call a poison center or doctor if you feel unwell. If yomiting occurs naturally.

have victim lean forward to reduce the risk of aspiration.

Do NOT induce vomiting unless directed to do so by medical personnel.

Never give anything by mouth to an unconscious person.

Delayed symptoms and effects: May cause gastrointestinal irritation. Signs/symptoms may include abdominal pain, stomach upset, nausea,

vomiting and diarrhea.

SECTION 5: Fire-fighting measures

Suitable extinguishing media

Foam, alcohol foam, CO2, dry chemical, water fog. Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.

Specific hazards arising from the chemical

Closed containers may rupture if exposed to fire or extreme heat due to build-up of steam pressure.

Special protective actions for fire-fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear. Water spray may be used to cool closed containers to prevent pressure build-up and possible rupture of containers.

SECTION 6: Accidental release measures

Personal precautions, protective equipment and emergency procedures

Avoid contact with skin, eyes and clothing. Ensure adequate ventilation.

Environmental precautions

Keep out of drains, sewers, ditches, and waterways.

Methods and materials for containment and cleaning up

Soak up with inert absorbent material. Sweep up and shovel into suitable containers for disposal.

SECTION 7: Handling and storage

Precautions for safe handling

Avoid contact with skin, eyes and clothing. Avoid breathing vapors, spray mists or sanding dust. In case of insufficient ventilation, wear suitable respiratory equipment.

Conditions for safe storage, including any incompatibilities

Keep container tightly closed. Keep out of the reach of children. Do not freeze. Product will not recover.

SECTION 8: Exposure controls/personal protection

Control parameters

CAS: 34590-94-8

Dipropylene glycol methyl ether

ACGIH (USA): 100 ppm, (ST) 150 ppm TLV® inhalation; Cal/OSHA: 100 ppm, (ST) 150 ppm PEL inhalation; NIOSH: 100 ppm, (ST) 150 ppm REL inhalation; OSHA: 100 ppm PEL inhalation; 600 mg/m3 PEL inhalation

Appropriate engineering controls

If user operations generate dust, fumes, gas, vapor or mist, use process enclosures, local exhaust ventilation or other engineering controls to keep worker exposure to airborne contaminants below any recommended or statutory limits.

Individual protection measures, such as personal protective equipment (PPE)

Pictograms





Eye/face protection

Safety glasses with side-shields.

Skin protection

Protective gloves and impervious clothing.

Body protection

Wear suitable protective clothing.

Respiratory protection

Where risk assessment shows air-purifying respirators are appropriate use a full-face particle respirator type N100 (US) or type P3 (EN 143) respirator cartridges as a backup to engineering controls. If the respirator is the sole means of protection, use a full-face supplied air respirator. Use respirators and components tested and approved under appropriate government standards such as NIOSH (US) or CEN (EU).

Environmental exposure controls

Emissions from ventilation or work process equipment should be checked to ensure they comply with the requirements of environmental protection legislation. In some cases, fume scrubbers, filters or engineering modifications to the process equipment will be necessary to reduce emissions to acceptable levels.

SECTION 9: Physical and chemical properties

Information on basic physical and chemical properties

Appearance/form (physical state, color, etc.)

Odor pH Melting point/freezing point

Initial boiling point and boiling range

Flash point
Evaporation rate
Flammability (solid, gas)

Vapor density

Vapor density Relative density Solubility(ies)

Auto-ignition temperature

Viscosity

Explosive properties

Liquid
Acrylic.
8.3-9.3
32°F / 0°C
212°F / 100°C
None (closed cup)
Slower than ether
Not applicable.
Heavier than air

9.10 lb/g Water None 102-105KU None

SECTION 10: Stability and reactivity

Reactivity

No specific test data related to reactivity available for this product or its ingredients.

Chemical stability

Stable under recommended storage conditions.

Possibility of hazardous reactions

Under normal conditions of storage and use, hazardous reactions will not occur.

Hazardous polymerization does not occur.

Conditions to avoid

No data available.

Incompatible materials

No data available.

Hazardous decomposition products

No data available.

SECTION 11: Toxicological information

Information on toxicological effects

Acute toxicity

Likely Routes of Exposure: Eye contact. Skin contact. Inhalation. Ingestion.

Skin corrosion/irritation

May cause skin irritation. Signs/symptoms may include localized redness, cracks, swelling, dermatitis and itching.

Serious eye damage/irritation

May cause eye irritation. Signs/symptoms may include redness, swelling, pain, tearing, burning, blurred or hazy vision.

Respiratory or skin sensitization

No data available.

Germ cell mutagenicity

No data available.

Carcinogenicity

No data available.

Reproductive toxicity

No data available.

Summary of evaluation of the CMR properties

No data available.

STOT-single exposure

No data available.

STOT-repeated exposure

No data available.

Aspiration hazard

No data available.

Additional information

No data available.

SECTION 12: Ecological information

Toxicity

No data available.

Persistence and degradability

Dipropylene glycol monomethyl ether: Biodegradability aerobic - Exposure time 28 d Result: 76 % - Readily biodegradable (OECD Test Guideline 301F)

Bioaccumulative potential

Does not bioaccumulate

Mobility in soil

No data available.

Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

Other adverse effects

No data available.

SECTION 13: Disposal considerations

Disposal of the product

Dispose of contents in accordance with local regulations.

Disposal of contaminated packaging

Dispose of containers in accordance with local regulations.

Waste treatment

Dispose of contents/containers in accordance with local regulations.

Sewage disposal

Dispose of contents/containers in accordance with local regulations.

Other disposal recommendations

Dispose of contents/containers in accordance with local regulations.

SECTION 14: Transport information

DOT (US)

Not dangerous goods

IMDG

Not dangerous goods

IATA

Not dangerous goods

SECTION 15: Regulatory information

Safety, health and environmental regulations specific for the product in question

New Jersey Right to Know Components

Common name: DIPROPYLENE GLYCOL METHYL ETHER

CAS number: 34590-94-8

Pennsylvania Right to Know Components


Chemical name: Propanol, (2-methoxymethylethoxy)-

CAS number: 34590-94-8

US federal regulations

CERCLA/SARA Hazardous Substance- Not applicable

HMIS Rating



NFPA Rating



SECTION 16: Other information

Do not freeze. Product will not recover.

Further information/disclaimer

While the description, data, and information contained herein are presented in good faith and believed to be accurate, it is provided for guidance only. Because many factors may affect application/use, it is recommended that you make tests to determine the suitability of a product for your particular purpose prior to use. No warranties of any kind, either expressed or implied, including warranties of merchantability or fitness for a particular purpose, are made regarding the product described, data, or information set forth, or that the product, data, or information may be used without infringing the intellectual property rights of others. In no case shall the description, information, or data provided be considered a part of our terms and conditions of sale. Further, you expressly understand and agree the description, data, and information furnished herein are provided gratis and we assume no obligation or liability for the description, data, and information given or results obtained, all such being given and accepted at your risk. The content of this SDS (a.k.a. MSDS) is copyrighted [(c) PFI]. This SDS may be shared, without changes, and no changes to the PFI content are authorized. Updates to all PFI SDS documents must be obtained directly from PFI. See Section 1 for PFI contact and website information. (14 JUNE 2018)