



Certificate  
of  
Analysis

**Product #**

**10-855**

**Premier Finishes, Inc.**

**Super-Prep**

PHYSICAL CHARACTERISTICS

<b>Weight per gallon:</b>	<b>10.88</b>
<b>% Solids by weight:</b>	<b>42.05</b>
<b>% Solids by volume:</b>	<b>24.42</b>
<b>PH:</b>	<b>8.0 – 9.0</b>
<b>Viscosity - Krebs:</b>	<b>95 - 100 KU</b>
<b>Flash Point (closed cup):</b>	<b>None</b>
<b>Spread Rate:</b>	<b>392 sq. ft. @ 1 mil</b>
<b>Material VOC:</b>	<b>0.03 lb. / gal.</b>
<b>Coatings VOC (-water):</b>	<b>0.14 lb. / gal.</b>
<b>Delta E:</b>	<b>.5</b>

Application Specifications

**Method:** Use at temperatures above 50 degrees F. Apply with airless sprayer, brush, or roller. Brush dust or dirt off application surface prior to application.

**Reduction:** None. Product is bucket ready.

Special Notes

**Please read the SDS before using this product.**

**Shelf life:** Six months – please rotate stock on a regular basis. Do not freeze. Product will not recover.

**Regulatory status:** This product is not considered a hazardous waste under current RCRA regulations. This product does not contain, nor is it manufactured using ozone depleting substances as listed under Section 611 of the Clean Air Act.

**PremierFinishes.net**

29MAY2018