

Certificate Of **Analysis**

Product # 10-887

Premier Pro-Builder's Series Hi-Build-Multi-Surface Latex Flat

Premier Pro-Builder's Series Multi-Surface Latex Flat Interior Wall Paint is a fast drying, hi-build multi-surface coating used to seal, prime and finish drywall, wall-board, plaster, masonry and wood. Premier Pro Builder's Series Flat Latex provides a durable, clean, white finish with outstanding hold-out when used as a under-coat for texture, or smooth-wall finishes. As a primer, TUFFKOTE seals and primes surfaces with excellent hide and hold-out, providing a uniform surface for finish coats. Finally, this versatile, Eco-Friendly product can be used as a low cost, Hi-build, wash able flat interior paint with good coverage and hide. Premier Pro Builder's Series Interior Flat is very economical to use providing the professional painter with one easy-to-apply product that does it all.

PHYSICAL CHARACTERISTICS

Weight per gallon: 11.27 % Solids by Weight: 48.04 %Solids by Volume: 30.06 PH:

8.5-9.5 Viscosity Krebs: 105 KU Flash Point (closed cup): none

Spread Rate: 481 sq. ft. @ 1 mil Material VOC: 0.15 lb /

Coatings VOC (-water): 0.42 lb / Delta E: .5

Application Method: Product can be applied by brush, airless or assisted-airless spray.

Reduction: Water-if necessary